DEVONagent Pro

VERSION 3.11.4

DOCUMENTATION

© 2001-2020 DEVONtechnologies

TABLE OF CONTENTS

READ ME **4**

The DEVONagent Pro Advantage 5
System Requirements 6
Installing, Updating, Removing 6
Trial Restrictions 7
Version History 7
License Agreement 16
Credits 16

GETTING STARTED **17**

Why use DEVONagent Pro? 17
When to use DEVONagent Pro? 17
DEVONagent Pro at a Glance 18
First steps with DEVONagent Pro 19

COMMON TASKS **20**

How to find on the Internet 20
How to search beyond Google 21
How to customize DEVONagent Pro 21
How to set up a search set to crawl feeds 22
How to run a search automatically 23
How to archive search results 23

QUERIES **25**

Operators 25
Designing a search query 27

SEARCH SETS **29**

What are search sets? 29
Choosing a search set 29
Creating and managing sets 30
Sharing sets 31
General tab 31
Advanced tab 33
Sites tab 34
Plugins tab 35
Actions tab 36
Schedule tab 37

MENUS **38**

The DEVONagent Pro menu 38
The File menu 39
The Edit menu 41
The Data menu 41
The Sort menu 43
The View menu 43
The Web menu 44
The History menu 46
The Go menu 46
The Window menu 47
The Services menu 47
The Scripts menu 48
The Help menu 48
The Dock menu 49

WINDOWS AND PANELS **51**

Search window 52
Web browser 59
Archive window 66
Search sets 68
Plugins and scanners 68
Downloads 71
Preferences 72
Assistant 72

PREFERENCES **75**

General 75
Search 77
Menu extra 78
Web 79
Tabs 81
Bookmarks 81
Email 82
Update 82

MENU EXTRA **84**

SCRIPTS **85**

Introduction 85
DEVONagent Pro's Scripts menu 86
Automator 88

PLUGIN DEVELOPMENT **89**

Creating Your Own Plugins 89
XML and JSON Keys 92

TROUBLESHOOTING **97**

DEVONagent Pro behaves irrationally 97
Problems interacting with DEVONthink 97

TECHNOLOGY **99**

General Concept 99
Features 99
Structure 99
Applications 100

OTHER PRODUCTS **101**

Overview 101
DEVONthink 101
DEVONagent 101
DEVONsphere 102
Needful Things 102

APPENDIX **103**

Glossary 103
FAQ (product-specific) 104
List of Search Sets 105
List of Plugins 106
List of Scanners 112
Log message codes 113

READ ME

IN THIS CHAPTER

The DEVONagent Pro Advantage	5
System Requirements	6
Installing, Updating, Removing	6
Trial Restrictions	7
Version History	7
License Agreement	16
Credits	16

Web Searching: Fed up with Web searches that return loads of useless links? Using advanced search techniques, DEVONagent Pro takes on all those tedious search-and-review tasks, releasing you to concentrate on relevant results.

THE DEVONAGENT PRO ADVANTAGE



WHY DEVONAGENT PRO?

Using advanced search techniques, DEVONagent Pro takes on all those tedious search-and-review tasks, releasing you to concentrate on relevant results. It assists you in

- finding,
- collecting, and
- organizing

information from the Web or your DEVONthink Pro Office databases with a powerful and flexible search architecture. It also features a powerful, research-oriented web browser and simple built-in archive, and tightly integrates with DEVONthink.

WHAT DEVONAGENT PRO DOES FOR YOU

- Using both standard and specialized search engines, DEVONagent Pro intelligently summarizes the results -- fast!
- Alternatively, DEVONagent Pro shows you an even larger number of search results using its unique graphical topic map.
- DEVONagent Pro support your research while browsing the Web, e.g., by listing all objects such as images, linked documents, or outgoing links embedded into a viewed page.
- DEVONagent Pro archives your search results with a single click or sends them to your DEVONthink database.
- Instead of making you repeat actions, DEVONagent Pro performs those actions for you. Combine search sets, schedule searches, etc., to create your very own personalized search assistant.

PERFECT INTEGRATION

- DEVONagent Pro integrates seamlessly with DEVONthink. With just one click, archive your search results, webpages, and other information grabbed from the Web to your DEVONthink database.
- Select text in any application and use DEVONagent Pro's Services menu or a contextual menu item to search for it. The Menu Extra keeps DEVONagent Pro at your fingertips.
- Use various actions, including notifications and AppleScript, to inform you of search results, then send them to either DEVONthink or the application of your choice to process them any way you wish.

Learn more about why you should use DEVONagent Pro, when you should use it, and how to run your first query: See also p. 17ff

SYSTEM REQUIREMENTS

Every Mac running OS X Yosemite or later. In addition, a fast Internet connection is highly recommended.

INSTALLING, UPDATING, REMOVING

Just move the DEVONagent Pro application package to the Applications folder or any other directory you have access to. Please note that OS X Services and the connection to DEVONthink work only for applications installed into one of the Applications folders, and that logout and login or a restart is required after installation.

To update an existing version of DEVONagent Pro, simply copy the application package from the disk image to your `Applications` folder, replacing the old version. Your database(s) will not be affected.

If you would like to switch from the Mac App Store variant of DEVONagent Pro to one directly downloaded from the DEVONtechnologies website, you can do so at any time. The official version will accept your Mac App Store receipt as a valid license. Copies not downloaded from the Mac App Store also allow you to buy an upgrade to a higher edition or version (if available).

To remove DEVONagent Pro traces from your computer, trash the following files and folders (~ represents your home folder):

- DEVONagent Pro
- `~/Library/Application Support/DEVONagent Pro`
- `~/Library/Contextual Menu Items/DEVONagent Pro CM.plugin`
- `~/Library/Preferences/com.devon-technologies.agent.*`

Depending on whether you have installed the following extras or not, remove them, too:

- The product-specific scripts in `~/Library/Scripts/` and `~/Library/Workflows/`
- The contextual menu plugin in `~/Library/Contextual Menu Items/`
- The legacy Dashboard widget

> Note: Depending the version of macOS you are using, some files may or may not be installed on your machine.

TRIAL RESTRICTIONS

Unregistered DEVONagent Pro runs for 60 hours of non-continous runtime or 30 days, whichever is later. Close the app to stop the clock from ticking and re-open later to continue your evaluation. The menu extra is restricted to 100 searches until DEVONagent Pro is registered.

VERSION HISTORY

New Improved Fixed Removed

VERSION 3.11.4

This release brings many fixes and improvements, including support for Apple Silicon Macs. Preview or display a slideshow of selected search results via Quick Look, and find up to 10,000 results with search sets. To help find related web pages, the *See Also* inspector now uses a page's keywords. We added support for importing bookmarks from the Brave browser and we improved RSS feed handling for increased compatibility with certain sites, e.g., Google Alerts. Lastly, we included many fixes and improvements in performance and reliability.

- Added a new command *View > Quick Look* and an alternate command, *View > Slideshow* (shown when pressing the *Shift* key), for use with selected search results.
- Added support for Apple Silicon Macs.
- Added support for the Brave browser in *Preferences > Bookmarks*, *File > Import*, and *Windows > Search Sets*.
- Added new AppleScript command `get favicon of`.

- Cosmetic changes made for macOS Big Sur.
- A `filetype:` operator can be added to a search if it's supported by the search engine, e.g., Google.
- A search can now return up to 10,000 results instead of 1,000.
- The *See Also* inspector of browser windows now uses the keywords of a page to find similar results on the web.
- Improved the HTML-to-text conversion in case of websites containing all text inside `NOSCRIPT` tags, e.g., our Discourse forum.
- The default encoding is now UTF-8 when none is specified by the site.
- Updated plugins: *Web*, *Computer Science > ACM Digital Library*, *References > Internet Public Library*, *References > SEC*.
- Updated Search Sets: *Marketing*.
- RSS feeds scanner and feed handling improved making them more compatible to certain feeds, e.g., Daring Fireball or Google Alerts.

- Items downloaded via the *Download Manager* now have the `kMDItemWhereFroms` extended attribute set.
- Improved compatibility of multimedia files with the *Download Manager*.
- Added a `BaseURL` key to the plugin API to specify the base URL for relative links of JSON and XML results.
- Improved compatibility of the *DEVONthink Server* plug-in to DEVONthink 3.
- Improved *Open URL* service.
- Improvements to the HTML parser enhances processes like improved scanner compatibility with websites loading images dynamically or the AppleScript command `get embedded images of` in the Pro edition.
- The *Last Safari session* script displays an alert if the System Events application doesn't have full disk access.
- Improved handling of invalid arguments of AppleScript commands.
- To improve the performance and reduce battery usage, web views on inactive tabs are no longer updated.
- Background tasks now support automatic graphics switching, potentially increasing the battery life on dual GPU MacBooks.
- The *Support Assistant* now uses `https:`.
- Sending bug reports via MailMate is now supported.
- A notification is added to the system's notification center each hour during the last twelve hours of the trial.
- Improved the application registration mechanism.
- Improved overall reliability.

- DEVONagent Pro could crash in macOS Big Sur on Apple Silicon Macs after trying to print a page. Fixed.
- Rare crash after going to previous occurrences, e.g., via the button in the *Digest* tab of search windows. Fixed.
- Added workaround to alleviate crashes cause by the Adobe PDF Viewer plugin.
- Completions of a browser window's address bar were not closed after deactivating the application. Fixed.
- Temporary glitches could be seen in browser windows while exporting paginated PDFs. Fixed.
- Going to the previous or next result in the *Digest* tab of search windows did not work as expected with URLs containing highlighted results. Fixed.
- Conversion of HTML to text sometimes generated wrong titles of scanner objects or links. Fixed.
- Conflict of `get title of` AppleScript command. Fixed.
- Many open web views could crash the WebKit framework. Improved by reusing web views.
- Certain Atom-based RSS feeds were incompatible. Fixed.

- Rare search engine issue. Fixed.
- The automatic installation from the disk image could show a Finder alert on macOS Catalina and temporarily freeze the user interface. Fixed.
- The shortcut control in *Preferences > Menu Extra* wasn't working properly. Fixed.
- The welcome video of the *Support Assistant* didn't work anymore. Fixed.
- Plugins installed via the *Support Assistant* into subcategories were not immediately shown in the correct location without a restart. Fixed.

- Removed plugins: Bing.

VERSION 3.11.3

This maintenance release improves date parsing while searching, updates two search plugins, and fixes a crash with PDFs on macOS Mojave and later.

- Improved parsing dates in searches.
- Smart dashes, smart quotes, grammar and spell checking are now disabled by default in the plugin editor.
- Updated a plugin for searching for clinical studies.

- Fixed a crash related to highlighting occurrences in PDF documents (macOS Mojave and later).
- Fixed issues with WebKit (macOS Mojave and later).
- Fixed an issue with searching the Apple Listserv.

VERSION 3.11.2

This maintenance update for DEVONagent Pro brings optimizations, fixes, and macOS Catalina compatibility. Some changes made in searching, parsing content, and generating summaries now provide better results. Performance and reliability have been improved with several bug fixes. Lastly, some changes relative to DEVONthink 3 have been made, including support for searching the web sharing of DEVONthink Server 3.

- Added AppleScript command *download JSON from*.

- Updated the *DEVONthink Server* plugin for compatibility with DEVONthink 3.
- Updated the toolbar icons to the new icons for DEVONthink 3 and its databases.
- The *Default* stylesheet for RSS feeds has been modernized, including dark mode support.
- The available RSS stylesheets in *Preferences > Web* are now sorted.
- Long menu item titles now are more accurately shortened.
- Displayed sizes, e.g., in the *Download Manager*, are now based on 1000 instead of 1024. This is similar to sizes reported in the the Finder and other applications.

- After adding a new workspace, the command *Go > Workspace > Update* now updates the last added workspace, not the most recently used one.
- Renamed action script "File results in DEVONthink Pro" to *File results in DEVONthink*.
- An alert is displayed after trying to import Safari bookmarks or history without enabling *System Preferences > Security & Privacy > Full Disk Access: DEVONagent Pro* (macOS Mojave or later).
- Summaries and digest results are more precise due to being based on characters.
- Optimized object scanning in browser windows when the Objects inspector is visible.
- Improved date parsing.
- Improved fuzzy searching.
- Improved the *Video* scanner.
- Improved filtering of ads and Captchas.
- Improved the HTML parser.
- Improved the display of RSS feeds having only a date but no time.
- Improved scrolling speed in the browser (macOS Mojave or later).
- Improved Accessibility using modern macOS features.
- Replaced *Buy* button in the License dialog with *Your Account*.
- Added menu item *Help > Your Account*.
- The trial version now runs up to 30 days from the initial application launch and up to 60 non-consecutive hours of use.
- DEVONagent Pro is now notarized.
- Improved overall performance and reliability.

- Fixed a crash caused by the Adobe Acrobat PDF viewer plugin.
- Fixed crashes related to WebKit, including one involving Touch Bar support.
- Fixed an issue where images of 1×1 pixels found by the *Image* scanner were marked as corrupted in the *Inspector* of DEVONagent Pro browser windows.
- Fixed an issue where the application licensing could fail on some machines, e.g., ones with a replaced logic board.
- Fixed an issue with a stall on launch (macOS Catalina).
- Fixed an issue with a visual artifact in browser windows when toggling the *Inspector* or navigation panes.
- Fixed an issue with font selection in DEVONagent Pro's *Preferences*.
- Fixed an issue with memory management after importing `.opml` files.
- Fixed an issue with proximity operators in a search being incorrectly applied.
- Fixed an issue with scanners returning too many or invalid objects in browser windows when viewing pages with frames having invalid URLs.
- Fixed an issue with the background color of the *Properties* inspector.
- Fixed issues with the *Download Manager* (macOS Catalina).

- Fixed a memory leak of the *Support Assistant*.

- Removed *DEVONtech Forum* plugin.

VERSION 3.11.1

This maintenance release addresses a sporadic crash some users had when accessing the *Preferences* panel on macOS Mojave, as well as some visual artifacts in the interface. We have also added support for JSON RSS feeds and improved handling of RSS feeds in general. Overall reliability has been the primary focus of this release.

- Added support for JSON RSS feeds.

- Updated plugins: *Government > USA.gov, References > SEC*.
- Renamed the search option *Atom, RSS, RSD & RDF feeds* to *Atom, RSS & JSON feeds*.
- Improved handling of untitled RSS feed items.
- Improved overall performance and reliability.

- Fixed various visual artifacts including ones affecting tabs on search windows (macOS Mojave).
- Fixed an issue where opening the *License* panel could stall the application when a network connection was not available or reliable.
- Fixed an issue where an alert was not displayed after entering an incorrect license code.
- Fixed a crash and incomplete display of the window when accessing the *Preferences* panel (macOS Mojave).

VERSION 3.11

This release features fixes, including greater compatibility with macOS Mojave, as well as other improvements. We have reorganized the search sets and updated a number of plugins as well as the thumbnail galleries scanner. A new option allows you to group search sets for more easily managing your sets. You can now choose to install and update extras automatically in the Support Assistant. A change to parsing a web page's rendered HTML allows for better See Also, translation, and automation via AppleScript. VoiceOver support in the interface has been enhanced too.

- You can now create search set groups in *Windows > Search Sets*. The action menu in the *Search Sets* panel now has *New Group* and *New Set* options.
- Search sets can now be installed via *Help > Support Assistant*.
- Added an option to the *Support Assistant* for installing and updating extras automatically.

- Plugins updated: *Qwant*, *Yandex*, *Blogs > Google Blog Search*, *News > BBC News*, *News > Google News*, *News > Topix*, *News > World News Network*, *Patents > Google Patents*

- Search sets updated: *Marketing*, *Mac > Latest News*, and *Mac > Latest Software*.
- Scanners updated: *Thumbnail Galleries*.
- Renamed, merged, and reorganized the default search sets.
- Merged the *Advanced* and *Exclude* tabs of the *Search Sets* panel.
- Improved automatic selection of content of web pages after choosing *Remember Selection* from the contextual menu.
- The toolbar button *Share > Email* in a browser window uses the current website's title as the subject line.
- Improved adding URLs via drag-and-drop in the *Downloads* window and the *Sites* tab of a search set.
- Improved keyboard navigation in outline views of windows like *Archive* and *Search Sets*.
- Renamed *Go > Workspace > Update...* to *Update*. The last used workspace is now updated.
- Added tooltips to the buttons on the *Downloads* window.
- Tooltips in the menu extra results now update more quickly.
- Minor cosmetic adjustments made in *Search* windows and *Properties* inspector of browser windows.
- Improved VoiceOver support.
- Increased efficiency in handling of RSS feeds.
- Improved filtering and retrieval of links, especially in *Express* mode.
- Results from adsabs.harvard.edu and adsbit.harvard.edu aren't filtered as advertisements any longer.
- DEVONagent Pro now uses the rendered web page, instead of the underlying HTML code, as the source for *See Also*, translation, and the "text" AppleScript property.
- Improved support for search engines allowing parentheses.
- Improved support for filtering Cyrillic language results.
- Improved support for "robots.txt".
- Moved to HTTPS for *Web > Translate* as well as all URLs linking to our site.
- Much faster updating of Finder comments of files and folders (macOS El Capitan and later).
- Generating web page thumbnails uses a new service as Thumbshots will shut down November 15, 2018.
- Improved overall reliability, including greater compatibility with macOS Mojave.

- Fixed visual artifacts in menus and the *Preferences* window (macOS Mojave).
- Fixed an issue in *Express* mode, where adding a resource to DEVONthink didn't work correctly.
- Fixed an issue where error pages in browser windows didn't show the correct icon.
- Fixed an issue where importing or searching the Safari history didn't work (macOS Sierra and later).
- Fixed an issue where playing a video in the *Support Assistant* would continue playing audio after the window was closed.

- Fixed an issue where *Scripts > Window > Open Last Safari Session* didn't work correctly.
- Fixed an issue with automatically updating to the latest version.
- Fixed an issue with the English localization of *Edit > Speech > Start and Stop Speaking*.
- Fixed a rare issue with the HTML parser.
- Fixed a crash if the option to install extras automatically was enabled.
- Fixed a crash after closing a browser tab or window (macOS High Sierra).
- Fixed a rare crash caused by memory management.

- Plugins removed: IEEE Xplore, Technorati, Lucky Guess.
- Removed the option to subscribe to welcome tips.
- The download manager no longer sets Finder comments as it caused automation alerts on macOS Mojave.

VERSION 3.10

This release adds a new Google Scholar (Case Law) plugin and updates several other plugins and search sets. For quick queries, it now supports DuckDuckgo Bangs in the internal browser. We've enhanced the support for live streams with the webcam and video scanners and made it a bit easier to create a custom search plugin, pasting in code you may find on our forums. And as always, we have improved the performance and stability of DEVONagent Pro.

> Note: Starting with version 3.10 DEVONagent Pro requires macOS 10.10 Yosemite or later.

- Plugins added: Legal > Google Scholar (Case Law) plugin.
- Added support for DuckDuckgo Bangs in the browser's address bar.
- Added *Markdown* and *Formatted Notes* options to *Window > Search Sets > Actions > Add results to DEVONthink > Format*.
- Added *Clutter-free layout* option to *Window > Search Sets > Actions > Add results to DEVONthink*. Requires at least DEVONthink 2.9.17.
- Added support for XML with custom plugins.
- Added "DatesKeyPath" key (JSON and XML) to retrieve the date of the result.
- Added optional "method" AppleScript parameter to specify the HTTP method when downloading documents.
- Added "last downloaded response" AppleScript property to retrieve the last HTTP-Status code and more.

- Plugins updated: Patents > Google Patent Search, References > British Library plugins, News > BBC News, News > Reuters, News > RocketNews, Legal > FindLaw, References > SEC.
- Search sets updated: Marketing, Apple (Feeds), Blogs.
- Video and webcam scanners work better with live streams.

- Creating a new plugin no longer requires a URL, making it easier to create a plugin with code copied from our forum.
- If you have selected to download updates automatically, *Update On Quit* will be displayed depending on the current progress of DEVONagent. Choosing this menu item will display a window about the pending update.
- In the plugin editor, changing the default keywords of a plugin now resets the user customized keywords as well.
- The "paginated PDF" AppleScript property uses the last used print settings and sets the title.
- Fonts of *Preferences > General* can be reset by holding the ⌥ Option key.
- Improved script *Scripts > E-mail > Current URL*.
- Improved performance of scanner objects, browser window, search windows, and the *Download Manager*.
- Improved character encoding support.
- Improved filtering of social bookmarking links.
- Using *Help > Report Bug* with the ⌥ Option key held creates an extended bug report including the installation path and startup volume format.

- Fixed an issue where an *Express* search didn't always return all results.
- Fixed an issue where exporting a report required a .pdf extension, regardless of the previously selected format.
- Fixed an issue where *Preferences > Menu Extra* mounted volumes added to the user's startup items.
- Fixed an issue where selecting a different scanner in browser and search windows caused an exception (macOS 10.9 through 10.12)
- Fixed an issue where the *Express* option of search sets was disabled when the secondary query was "*".
- Fixed an issue where the number of scanner objects for a search result was not always identical to the number of scanner objects shown in the scanner bar.
- Fixed an issue with sending formatted notes or Markdown documents to DEVONthink.
- Fixed some minor cosmetic issues with the user interface.
- Fixed a rare crash caused by background processes.

- Disabled Twitter plugin on macOS High Sierra as access to system-wide social accounts is no longer possible.
- Removed script *Scripts > E-mail > Current URL (Mail)*.
- Removed plugins *Info (News)*, *Info (Images)*, and *Info (Video)*.

VERSION 3.9.8 ... 1.1

...

VERSION 1.0

Initial release.

LICENSE AGREEMENT

PLEASE READ THIS LICENSE CAREFULLY BEFORE USING THIS SOFTWARE. BY USING THIS SOFTWARE, YOU ARE AGREEING TO BE BOUND BY THE TERMS OF THIS LICENSE AGREEMENT. IF YOU DO NOT AGREE TO THE TERMS OF THIS LICENSE, DELETE THE SOFTWARE OR RETURN THE SOFTWARE AND RELATED DOCUMENTATION TO DEVONTECHNOLOGIES, LLC.

1. License: The application and other components (sound and graphics) accompanying this License, whether on disk, in read only memory, or on any other media (the "Software"), and the related documentation are licensed to you by DEVONtechnologies. You own the disk on which the Software is recorded but DEVONtechnologies and/or DEVONtechnologies' Licensor(s) retain title to the Software and related documentation. This License allows you to non-simultaneously use the Software on multiple computers by the same person.

2. Restrictions: The Software contains copyrighted material, trade secrets and other proprietary material and in order to protect them you may not decompile, reverse engineer, disassemble or otherwise reduce the Software to a human-perceivable form. You may not sub-license, modify, rent, lease, or create derivative works based upon the Software in whole or in part. You may not distribute the Software in any form, including, but not limited to, electronic information service distribution, bulletin board distribution, and magnetic or optical medium distribution.

3. Disclaimer of Warranty on Software: You expressly acknowledge and agree that use of the Software is at your sole risk. The Software and related documentation is provided "AS IS" and without warranty of any kind.

4. Limitation of Liability: UNDER NO CIRCUMSTANCES INCLUDING NEGLIGENCE, SHALL DEVONTECHNOLOGIES BE LIABLE FOR ANY INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES THAT RESULT FROM THE USE OR INABILITY TO USE THE SOFTWARE OR RELATED DOCUMENTATION. In no event shall DEVONtechnologies' total liability to you for all damages, losses and causes of action (whether in contract, tort (including negligence) or otherwise) exceed the amount paid by you for the Software.

Apple, Carbon, Classic, Cocoa, ColorSync, Darwin, OS X, QuickTime, Quartz and all other registered names are trademarks of their respective owners.

CREDITS

SMTPMAILDELIVERY

Dante Palacios

The SMTPMailDelivery library is used according to the MIT License.

VIDEO JS

Copyright © 2010 Zencoder, Inc.

The Video JS player is used according to the LGPL v3.

GETTING STARTED

IN THIS CHAPTER

Why use DEVONagent Pro? 17
When to use DEVONagent Pro? 17
DEVONagent Pro at a Glance 18
First steps with DEVONagent Pro 19

This chapter helps you get started with DEVONagent Pro. It explains why and when to use DEVONagent Pro, and gives you step-by-step instruction in how to run a first query.

WHY USE DEVONAGENT PRO?

A common misconception is that DEVONagent Pro is a simple front-end to Google or Bing. This is far from the truth. DEVONagent Pro is a very capable Internet research assistant that handles tedious research tasks such as weeding out bad search results, spotting linked documents, and finding information on a webpage.

Searches with DEVONagent Pro take longer than quick searches on a Web search engine because DEVONagent Pro downloads each resulting page instead of only presenting you with a link to it. DEVONagent Pro searches also return fewer results since DEVONagent Pro filters broken links, advertisements, and outdated pages. This feature actually saves time because you do not have to do all this manually.

Reasons for using DEVONagent Pro include:

- You get much better search results.
- You don't have to do all the tedious, repetitive tasks involved in a search; DEVONagent Pro does them for you, freeing you to spend more time on meaningful, more important tasks.
- You can search more specifically using DEVONagent Pro's advanced operators and search sets.
- You get the results in a much more natural presentation in the *Digest*.
- You can archive interesting searches and review or expand those searches on another day.
- You use a specialized web browser with research-centric additions, e.g., the sidebar.
- You can use DEVONagent Pro to run regular searches when you are not at the computer, and it will present the results, if any, when it has finished.

WHEN TO USE DEVONAGENT PRO?

DEVONagent Pro outperforms other Web search engine, especially for research purposes, but it is not necessarily a useful tool for simple, every-day searches. Because DEVONagent Pro downloads all results to your Mac to analyse and post-process, a search run takes between a few seconds and several minutes.

Use DEVONagent Pro for:

- Getting answers to a question
- Finding all available data about a subject
- Searching multiple search engines and websites with just one click
- Scraping objects from webpages, e.g., images, email addresses, or Atom/RSS/JSON feeds
- Keeping up-to-date on a subject, e.g., with scheduled searches

Don't use DEVONagent Pro for:

- Finding the webpage of company X or product Y
- Finding a very specific image or video
- Finding the definition for a word quickly, e.g., on Wikipedia

DEVONAGENT PRO AT A GLANCE

DEVONagent Pro hides complex functionality but makes it available when you need it. Here's a quick overview over the three main windows DEVONagent Pro uses and what window elements they offer.

SEARCH WINDOWS



You use search windows to enter your query (search term), start the search, and view the results. See also p. 52ff

WEB BROWSER WINDOWS



You use web browser windows like any other web browser plus DEVONagent Pro's research-centric additions. See also p. 59ff

THE ARCHIVE WINDOW



You use the archive to save search results and recall them later. See also p. 66ff

FIRST STEPS WITH DEVONAGENT PRO

A first search: While DEVONagent Pro is a real power tool, searches do not need to be overly complex. Running a simple search using DEVONagent Pro is no more complicated than using Google or Bing.

- Run a first search with a few simple steps

The next steps: Now that you know how to run a first search you can take the next steps unaided. Here are a few chapters for you to continue exploring DEVONagent Pro:

- More common tasks
- How to formulate a good query
- How to create your own search sets
- Customize DEVONagent Pro to your preferences
- Create your own plugin if your search engine is not supported

Finally, DEVONagent Pro and the DEVONtechnologies website offer additional information and assistance:

- Open the Support Assistant for on-screen tutorials and regularly updated tips
- Read the FAQ
- Visit our lively user forum

COMMON TASKS

IN THIS CHAPTER

How to find on the Internet 20
How to search beyond Google 21
How to customize DEVONagent Pro 21
How to set up a search set to crawl feeds 22
How to run a search automatically 23
How to archive search results 23

This chapter explains common tasks in DEVONagent Pro in a step-by-step way and points you to related topics.

HOW TO FIND ON THE INTERNET

DEVONagent Pro's main objective is to find stuff on the Internet. It does so by sending a query (search term) to a selected set of search engines, e.g., Google, collecting the results, analyzing them, and presenting them to you.

You tell DEVONagent Pro which search engines to use by selecting a plugin (contains instructions telling DEVONagent Pro how to communicate with a search engine) or search set (combinations of multiple plugins and other options). DEVONagent Pro comes with a large number of pre-fab plugins and search sets already installed. See also p. 106ff



Step by step: You are trying to find information about the WikiLeaks disclosure of diplomatic cables.

- **Step 1:** Open a new search window with *File > New Search*.
- **Step 2:** Choose the search set you want to use in the magnifying glass pop-up menu: *Web (Fast)*
- **Step 3:** Enter your query (search term): wikileaks AND "diplomatic cables"
- **Step 4:** Click *Start*.

Click here to make DEVONagent Pro run the search.

The best choice for a simple but comprehensive search is the pre-fab *Web (Fast)* search set. It is a multi-purpose search set that sends your query to the three major search engines: Google, Bing, and Yahoo. Alternatively, you can choose plugins directly, e.g., the one for Google, in the magnifying glass pop-up menu.

DEVONagent Pro Advantage: You can use advanced Boolean operators. Doing so returns a pre-processed summary including extracted topics rather than just a simple list of links. In addition, DEVONagent Pro queries multiple search engines for you with one single click.

Next steps:

- Fine tune your search with the Settings tab
- Design a good query
- Learn more about the advanced Boolean operators
- Create your own search sets

Related topics:

- The search window explained
- List of pre-fab search sets
- List of built-in search engine plugins

HOW TO SEARCH BEYOND GOOGLE

DEVONagent Pro can not only run queries on Google and Bing, but comes with a large number of plugins that let it use less common search engines such as FindLaw, PubMed, or Highbeam.

Just choose the right plugin before you start your search from the magnifying glass pop-up menu in the search field.



Step by step: You are trying to find newspaper articles about the former German defence minister who had to resign because he copied large parts of his doctor thesis.

- **Step 1:** Open a new search window with *File > New Search*.
- **Step 2:** Choose the plugin to use in the magnifying glass pop-up menu: *References > Highbeam*
- **Step 3:** Enter your query (search term): "zu Guttenberg" plagiarism
- **Step 4:** Click *Start*.

DEVONagent Pro sends the results to the Highbeam article search engine and presents you with the results.

Click here to make DEVONagent Pro run this search for you.

Next steps:

- Design a good query
- Learn more about the advanced Boolean operators

Related topics:

- The search window explained
- List of pre-fab search sets
- List of built-in search engine plugins

HOW TO CUSTOMIZE DEVONAGENT PRO

Like most other Mac applications, DEVONagent Pro can be customized to better fit your needs. You adjust all of DEVONagent Pro's setting in its Preferences.



Step by step: You want to exclude all links to eBay from the results.

- **Step 1:** Open the *Preferences, Search tab*.
- **Step 2:** Click into the *Exclude Domains* field.
- **Step 3:** Add 'ebay.' (with the dot, but without the single quotes) to the list.

This filters all results with addresses containing the string 'ebay.'

Next steps:

- Set the other preferences to your needs
- Learn more about the other options in the DEVONagent Pro menu
- Learn more about the other options in the action menu

HOW TO SET UP A SEARCH SET TO CRAWL FEEDS

DEVONagent Pro not only queries search engines for you, it can also search on its own by "crawling" a specified list of webpages or news feeds and scanning them for the search term. This feature is handy when you have a number resources you want to watch, e.g., subject-specific news sites or feeds.



Step by step: You want to search one of the New York Times news feeds.

- **Step 1:** Click here to open the *Search Sets* window. Open it manually using *Window > Search Sets*.
- **Step 2:** Click the + button to create a new set. Name it, e.g., "New York Times".
- **Step 3:** Switch to the *Sites* tab.
- **Step 4:** Click here to open the New York Times RSS page in a new web browser window.
- **Step 5:** Show the Inspectors tab using *Web > Inspectors > Show* and switch to the tab.
- **Step 6:** Copy the address of any RSS feed of interest by right-clicking it and choosing *Copy* from the contextual menu.
- **Step 7:** Switch to the *Search Sets* window and paste it, e.g., by pressing ⌘*V*. or using *Edit > Paste*.

Repeat Steps 6 and 7 for any feeds that you want to add to your "New York Times" search set. You can now use this set like any other search set or plugin. Instead of querying any search engines, it will download the current state of all the feeds you have added and search them for occurences of your search term.

Next steps:

- Run a first query
- Design a good query
- Learn more about the advanced Boolean operators
- Run your search automatically

Related topics:

- More about search sets

HOW TO RUN A SEARCH AUTOMATICALLY

Search sets are not only collections of rules about how to run a search, they are also the key to research automation in DEVONagent Pro. Add a default query to a search set and set its scheduler to make DEVONagent Pro run the search when you're not around, e.g., in the middle of the night, and execute chosen actions when the search is completed.



Step by step: You want to run the "Marketing" search set automatically once every day and send the results to you by email.

- **Step 1:** Click here to have the *Search Sets* window opened and the "Marketing" search set selected for you.
- **Step 2:** Switch to the *Actions* tab.
- **Step 3:** Check *Send mail to* and enter your email address.
- **Step 4:** Switch to the *Schedule* tab.
- **Step 5:** Select *Daily* and set the time to, e.g., 9 a.m.

As the "Marketing" search set contains a default query on the *General* tab, you are done. Tomorrow morning at 9 a.m. DEVONagent Pro will automagically activate and run a search for the default query of the "Marketing" set. When it is finished, it will send a summary email to the specified email address.

> Note: Your Mac needs to be on at the time the search set is scheduled to run. DEVONagent Pro is not able to wake your Mac up from sleep mode.

Next steps:

- Learn more about actions
- Learn more about the schedule options

Related topics:

- Learn more about search sets

HOW TO ARCHIVE SEARCH RESULTS

After you have found good data on the Internet, it is likely you're only halfway to your desired outcome. You will want to keep the best results for future reference. For this reason, DEVONagent Pro comes with a built-in archive.



Step by step: You want to archive all results of a search run.

- **Step 1:** Run a search, e.g., with the Bing or Google plugin.
- **Step 2:** Choose *Data > Add All To Archive*.
- **Step 3:** The results have been saved to the *archive* in a group named after your query.

Step by step: You want to archive results from a search run.

- **Step 1:** Run a search, e.g. with the Bing or Google plugin.
- **Step 2:** Switch to the *Results* tab, e.g., by pressing ⌘*2*.
- **Step 3:** Select the results you want to archive.
- **Step 4:** Choose *Data > Add To Archive*.
- **Step 5:** The results have been saved to the *archive* in a group named after your query.

As an alternative to using *Data > Add To Archive*, *Data > Add All To Archive*, and *Window > Archive*, you can use the *Add*, *Add All*, and *Archive* toolbar icons of the search window. You may need to add the tools to the toolbar using *View > Customize Toolbar*.

Next steps:

- Work with the archive

Related topics:

- Adding results to DEVONthink

QUERIES

IN THIS CHAPTER

Operators 25
Designing a search query 27

DEVONagent Pro provides powerful Boolean operators that allow users to precisely define a search query.

Queries can range from uncomplicated one-word search terms to complex multi-term queries. The rules for formulating queries are simple. By studying the rules and the Boolean operators, and with a little practice, users can 'tell' DEVONagent Pro exactly what to look for in a search.

OPERATORS

PLUGIN/SET SELECTION

To quickly select which plugin or search set DEVONagent Pro uses, start the query with the name of the plugin or search set or keyword followed by a colon.

> **Example:** google:devonthink

CASE

Terms are NOT case sensitive. You may use capitalization for proper names in a query, but DEVONagent Pro will ignore case in interpreting the query.

PRECEDENCE OF TERMS

Search terms and associated operators will be interpreted from left to right, except as modified by including portions of the query within parentheses.

BOOLEAN OPERATORS

The operators (often called Boolean operators) are words or symbols that establish logical rules for the terms in the search query. These are:

- **term1 AND term2:** Contains term1 AND term2
- **term1 BUT term2:** Contains term1 AND term2
- **term1 OR term2:** Contains term1 OR term2
- **term1 XOR term2:** Contains term1 or term2, but not both
- **term1 EOR term2:** Contains term1 or term2, but not both
- **NOT term:** Does not contain term
- **"term1":** Contains the string term1, in exactly this form; uses fuzzy matching (e.g. "DEVON tech" matches also "DEVON-tech" or "DEVON++++tech"); accepts also the '*' operator, like 'BEFORE' but more precise.

Besides the classic Boolean operators, DEVONagent Pro features a number of operators usually only found in high-end databases. Use them as a replacement for AND and "quotes" to fine tune your query.

- **term1 NEAR term2:** term1 occurs 10 words or less before or after term2
- **term1 NEAR/n term2:** term1 occurs n or less words before or after term2
- **term1 BEFORE term2:** term1 occurs before term2
- **term1 BEFORE/n term2:** term1 occurs n or less words before term2
- **term1 NEXT term2:** term1 occurs right before term2 (shortcut for BEFORE/1)
- **term1 NEXT/n term2:** term 1 occurs n or less words before term2 (synonym for BEFORE/n)
- **term1 AFTER term2:** term1 occurs after term2
- **term1 AFTER/n term2:** term1 occurs n or less words after term2
- **term1 OPT term2:** term1 is mandatory but term2 is optional. If term2 is also found the result is ranked higher.
- **~term1:** Contains all words that begin or end with term1 (words containing term1 as a part of the word; depends on the queried search engine)

> Note: See chapter Designing a Search Query for examples on how to use all these operators effectively.

For convenience, some of these operators can also be abbreviated using commonly used symbols:

- **AND:** &, &&, +
- **OR:** #, ##
- **XOR:** #, ##
- **NOT:** !, -

> Note: The symbols above also are used by the Finder and Spotlight for searches. Enter the vertical ruler character for the OR operator by pressing ⇧7, ⇧\ or the appropriate keyboard combination for your keyboard layout.

WILDCARDS

You can replace parts of words with wildcards matching one, multiple, or a range of characters:

- **?:** Matches exactly one character.
- ***:** Matches none, one, or multiple characters.
- **[a-b]:** Matches one character of the range 'a' through 'b'.
- **[abc...] or [a|b|c|...]:** Matches one character out of the given list of characters.
- **[^...]:** Matches one character that is not contained in the given list or range.

> Note: Primary queries only support wildcards for sites, not for plugins or search engines.

SPECIAL RULES

To search for a word that is also the name of an operator, put the word inside quotation marks. The following example searches all four terms including the word "near":

> **Example:** Beach "near" Los Angeles

Existing "site:<domain.com>" operators in primary queries are removed before matching to facilitate searching sites using the Google, Bing, and Web plugins or search sets using them.

DESIGNING A SEARCH QUERY

Writing your query as simply and as precisely as possible is the key to good search results. Following are some tips on how to write a good query.

DESIGNING A GOOD QUERY

Suppose you want to search for information about the mercury contamination of fish, and to focus on information released by or referring to the United States Environmental Protection Agency.

One problem with trying a simple AND search for a group of words is that the Environmental Protection Agency is referred to in various ways: Environmental Protection Agency, EPA and E.P.A.

If we tried the search string

> **Example:** Environmental AND Protection AND Agency AND EPA AND E.P.A. AND fish AND mercury

we would probably get no results at all, as no single article would use all three terms for the environmental agency. And even if we were to get search results, we would get irrelevant results stemming from the terms environmental, protection and agency.

Here's a better way to design the query:

> **Example:** ("Environmental Protection Agency" OR EPA OR "E.P.A.")

which will pick up the variants in naming the agency in articles. Note that the two strings enclosed in quotation marks will now be treated as phrases. This reduces ambiguity. Also note the use of parentheses and the OR operator. We have now covered all three variants of common names used for the environmental agency. DEVONagent Pro will look for pages containing any one of those names.

Another potential ambiguity is created because it's possible that a large reference source might contain the word 'fish' in one section dealing with fishery resources, and contain the word 'mercury' in another section dealing with the history of barometers. We're simply not interested in that item. But if we use the NEAR operator between 'fish' and 'mercury' it's likely that we will get useful results, since this query places the space between the two terms at 10 words or less.

The refined query now becomes:

> **Example:** ("Environmental Protection Agency" OR EPA OR "E.P.A.") AND (fish NEAR mercury)

Notice that a second set of parentheses was used so that DEVONagent Pro doesn't wrongly interpret the query as requiring that both the environmental agency name and 'fish' must be NEAR 'mercury'. That confusion would be created if we wrote the query as:

> **Example:** ("Environmental Protection Agency" OR EPA OR "E.P.A." AND fish) NEAR mercury

Indeed, the refined search returned highly relevant pages. Of course, this search focused on literature about mercury contamination of fish in the United States. To change the geographical focus, one would simply replace the search strings in the first set of parentheses with, e.g., ("European Union" OR EU).

IMPROVING YOUR QUERY

Besides the typical Boolean operators AND, OR and NOT, DEVONagent Pro provides much more powerful NEAR, BEFORE and AFTER operators. Typically, only scientific high-end databases feature these operators, but DEVONagent Pro makes them available for Web research.

> Note: Because almost none of the Web search engines support these operators, DEVONagent Pro sends the simpler AND query to them and applies the more sophisticated operators to the resulting pages.

All three operators connect two search terms closer together than AND, but not as tightly as the phrase operator (double quotes). With the additional distance parameter (e.g., NEAR/5) you can fine tune search results until you get only the results you are looking for.

> **Example:** (steve NEAR/2 jobs) BEFORE (intel NEAR (imac OR macbook)) AND "San Francisco"

Connecting 'steve' and 'jobs' with NEAR/2 prevents getting result pages of some Steve looking for a job in his page footer. BEFORE makes sure it is a page that mentions Steve Jobs first, followed by the Intel Macs. Finally, the quotes around 'San Francisco' find only pages dealing with the city of San Francisco, not the city San Jose or a Brother Francisco mentioned elsewhere on the page.

Use the proprietary NEAR, BEFORE and AFTER operators when AND delivers too many results and quote marks delivers too few. Another example:

> **Example:** document AND management AND mac

This query run with the *Web (Fast)* search set deliveres good results. But, many are not what we are looking for. Among good pages, it also presents the Wikipedia article about OS X because it contains all three words. But, of course, this article is not at all about document management on the Mac. We can refine this query, however, using the special DEVONagent Pro operators:

> **Example:** document NEAR/2 management NEAR mac

This time, DEVONagent Pro returns fewer results, all of them dealing exactly with our search subject, document management for the Macintosh, because the three words must appear near each other in the text. In most cases, NEAR delivers more accurate results than AND.

FIRST PRINCIPLE OF A SUCCESSFUL QUERY

Make the query precise and unambiguous. DEVONagent Pro's tools for clarifying your query are clear and simple and will help you obtain a high percentage of useful results.

SEARCH SETS

IN THIS CHAPTER

What are search sets? 29
Choosing a search set 29
Creating and managing sets 30
Sharing sets 31
General tab 31
Advanced tab 33
Sites tab 34
Plugins tab 35
Actions tab 36
Schedule tab 37

The quality of a query relies not only on the entered search term, it also relies heavily on the selected settings. Search sets are collections of all the parameters (settings) related to a search run. Use search sets to quickly tweak your settings, depending on what you are searching for on the Internet. This ensures that you always get the best results.

WHAT ARE SEARCH SETS?

Search sets basically are collections of all the parameters related to a search run:

- A default query
- Follow links settings
- Filters and associated scanners
- Sites to scan or search
- Pluginsto use
- Actions to run when the search run is completed
- A schedule

Using these settings, you can create search sets specifically tailored for your research needs. For example, you could create your own sets for:

- Querying the U.S. Patent Office and WIPO databases, along with scanning some important websites related to patents
- Looking for articles related to DEVONtechnologies on Google, as well as some Mac news sites, with the search scheduled every three hours and programmed to send a summary to your email address
- Searching the most important medical databases, e.g., PubMed, Medscape and FDA, in a single search run
- Querying a number of general search engines like Google, MSN and Yahoo, but filtering out everything except pages with links to Office documents

CHOOSING A SEARCH SET

Choosing the search set that you want to use for a search run is easy: Click the magnifying glass icon in a DEVONagent Pro search field and choose a search set from the pop-up menu.

DEVONagent Pro comes with a number of predefined search sets, but you can easily create your own.

CREATING AND MANAGING SETS



Search sets can be edited, rearranged, exported, imported or deleted. DEVONagent Pro comes with a couple of useful predefined sets, which you can tweak to your needs. Or you can add new ones. Use *Window > Search Sets* to open the search set editor.

> Note: Some of the settings can also be adjusted on-the-fly in the *Settings* and *Advanced* tabs.

The search set editor shows a list of all defined search sets and allows you to add new sets or delete the selected set using the + and - buttons, just like in other Mac applications. Rearrange your search sets using drag-and-drop, and single-click the name of any set to change its name. Add groups via the *Action* or contextual menu to organize your search sets.

> Note: Some items can be dragged from one search set to another set, e.g., URLs from the sites tab.

To change the settings defined in a set, select it in the list and change the parameters in the right-hand pane. Switch between the areas, *General*, *Advanced*, *Sites*, *Plugins*, *Actions*, and *Schedule* by using the tabs above the parameter area.

SHORTCUT

To create a new search set with exactly the same settings as the current search run, click the + button next to the *Stop* button in the search window. This creates a new search set with exactly the same settings including the query as the default query.

ACTION MENU

The *Action* menu, available from the gear button below the search set list, gives you access to additional commands. See also p. 31ff

CONTEXTUAL MENU

The contextual menu gives you direct access to frequently used commands.

- **New Set:** Creates a new, empty search set.
- **New Group:** Creates a new group for organizing your search sets.
- **Duplicate:** Duplicates the selected search set.
- **Delete:** Deletes the selected search set. Attention: There is NO undo!
- **Import:** Creates new search sets based on imported files. You can import previously exported sets, as well as OPML files, Camino, Firefox, Chrome, OmniWebor Safari bookmarks or the Safari history file. For OPML, bookmarks and history files, DEVONagent Pro creates a new search set with all URLs imported to the *Sites* list.
- **Export:** Exports the selected search sets as separate files. Exported sets get the file name extension '.agentSet' and are XML/plist files. You can import them into DEVONagent Pro by double-clicking them in the Finder.

SHARING SETS

You can easily share search sets with other DEVONagent Pro users. Export sets using either the *contextual menu*, the *File > Sets* menu command, or by simply dragging them e.g. to the Desktop. You can email exported sets and import them again into DEVONagent Pro simply by double-clicking them in the Finder.

GENERAL TAB

On the *General* tab, you define the main parameters for this search set such as the default query, which filter and which scanner to use.



QUERIES

Default Query: Define a default query for this search set. DEVONagent Pro will automatically fill the query field with the default query when you select this search set. This is especially useful if you are using either the same query every time you use this search set or if you are running this set on a schedule.

> **Example:** esa AND (mission NEAR "venus express")

Read more about formulating a query here:
See also p. 25ff

Secondary Query: When you enter something here, the primary term (the one entered or the default query) is only used for querying the search engines, not for accepting or rejecting pages. Without a secondary query, DEVONagent Pro uses the primary query for both querying search engines and post-filtering results.

You can use secondary queries for different terms for querying the search engines and accepting/rejecting pages. Although the primary query is restricted to 10 words, the secondary query is not restricted.

> **Example:** Use the asterisk '*' as your default query to match everything, e.g, when scanning a list of websites or Atom/RSS/JSON feeds; this option is not applicable with search engine plugins, only with the *Sites* list. To accept all pages delivered by a primary query, use the asterisk '*' as the secondary query.

FOLLOW LINKS

These options tell DEVONagent Pro to follow promising links on HTML pages and in news feeds. Links are considered 'promising' if they match the entered or default query. If you enter an additional query into the text field below the pop-up menu instead, this query is used to indentify promising links.

> **Example:** The query 'Devonian Period -County' follows links containing 'Devonian' or 'Period' but not containing 'County'.

In the pop-up menu choose which links you want DEVONagent Pro to follow:

- **Off:** Follows no links.
- **All:** Follows all promising links.
- **On Same Host:** Follows all promising links leading to the same server (domain).
- **In Same Directory:** Follows all promising links leading to pages in the same directory.
- **In Subdirectories:** Follows all promising links leading to pages in the same directory or its sub-directories.

On the right-hand side of the pop-up menu select how many levels deep you want DEVONagent Pro to follow links. One or two levels generally make sense, more is often overkill.

Use the text field below the slider to provide an additional search query that defines which links DEVONagent Pro follows. Use this option to fine tune your settings if you find that DEVONagent Pro follows meanlingless links due to the construction of the result pages. Generally, you should leave this field blank and let DEVONagent Pro follow all links matching the entered or default query; the automatically chosen term is displayed in this case.

> **Example:** Enter '*' to let DEVONagent Pro follow all links, regardless whether or not their text description matches the query.

EXPRESS SEARCH

Check *Express Search* to enable 'express' mode. In 'express' mode DEVONagent Pro returns results fast, but does not filter the results. If unchecked, DEVONagent Pro operates in 'agent' mode, which is slower but returns post-filtered results and is a more precise and powerful tool.

> Note: Scanners and secondary search terms, the similar pages filter, and following links require 'agent' mode. Some plugins may also require 'agent' mode; others may not support 'express' mode.

LANGUAGE

Language: Use this pop-up menu to filter out all pages that do not match the selected language (Dutch, German, English,...) or script system (Arabic, Greek, Hebrew,...) Instead of simply looking for language tags, this filter actually analyzes the page itself.

Ignore Diacritics: Check this option to automatically convert diacritics for analysis into a normalized form. This also finds pages that contain German umlauts, French or Czech accents, or other diacritical characters.

> Example: Uncheck *Ignore Diacritics* to search for a word with accented characters when you definitely don't want to find the unaccented variant.

Fuzzy: Check to search 'fuzzy'. This also finds words with similar but not identical spelling, e.g., 'gray' instead of 'grey'.

FILTERS, SCANNERS,...

Filters: Check the following filters to automatically filter out special pages you don't want to include in the results list:

- **Similar Pages:** Filters out pages similar to results previously found in the search run.
- **Archived Pages:** Filters out all pages already stored in the archive. DEVONagent Pro compares only the URLs in this case, not the actual page content.

Scanner: Scanner plugins post process and filter the list of found pages by formal criteria. Read more about scanners in the appendix.

> Example: Use this powerful feature unique to DEVONagent Pro to filter, for example, all pages except those containing a thumbnail gallery, linking to Office documents, or containing email addresses.

COMMENTS

Enter a brief description for a search set here. This description is shown in the tooltips of the magnifier pop-up menu in a search window.

ADVANCED TAB

On the *Advanced* tab, you define in which parts of webpages DEVONagent Pro searches, which type of files it searches, and whether it accepts all pages or only new results.



SEARCH IN

Choose which parts of a document DEVONagent Pro searches for the query. Not all file types have all characteristics.

- Title
- Text
- URL
- Keywords

- Description
- Objects

FILES

Choose which file types DEVONagent Pro searches and accepts as results.

- HTML & XHTML pages
- Atom, RSS & JSON feeds
- Plain text documents
- PDF & PostScript documents
- OpenOffice & StarOffice documents
- Rich text documents
- Microsoft Word documents

RESULTS

Choose if you want DEVONagent Pro to accept results only from new pages or from all found pages.

- **All pages:** Always accept all matching pages.
- **Only new pages:** Accept only new matching pages.

DEVONagent Pro keeps an internal log of found results to recognize which are new. It also lists the number of results stored in the log. To clear the internal log, click the *Reset* button.

EXCLUDE

The *Exclude Domains* and *Exclude Links* fields allow you to explicitly exclude domains and links from being used or followed when you use this search set. Add the domains or links that you want to be excluded into the text fields. You can use asterisk (*) wildcards to include e.g. all subdomains or partial links.

SITES TAB

The *Sites* tab allows you to define a list of webpages that DEVONagent Pro scans (crawls) or searches when you use this search set. DEVONagent Pro downloads each of these pages and tests whether it matches your query, just like a private little Google. Alternatively it runs a site search on it using common search engines. Use it together with the default query to scan your frequently visited pages for important keywords.



MANAGING THE SITES LIST

To add a page to the list, enter the URL into the location field at the bottom of the window. If the page requires a user name and password, enter them into the appropriate fields. Click the + button to add the page. To remove a page, select it in the list and click the - button.

You can also use drag-and-drop or copy/paste to add URLs to the sites list, and use the contextual menu to open the page in a browser window or copy the URL. This also adds the title of the page to the *Info* column when possible. You can copy URLs in this list to the clipboard or drag them to other applications, too.

You can use ranges like [01-31] or [1-31] to quickly add whole ranges of URLs. Add "https://www.classicfm.nl/playlist/per-dag/201202[01-29]" to add all playlist from .../20120201 through .../20120229.

Uncheck a page to exclude it temporarily from being scanned; check the page to include it in the next search run.

CRAWL VS. SEARCH MODE

DEVONagent Pro can either crawl (scan) or search sites added to the list. You can set this option individually for each site.

- **Crawl:** Downloads the page and adds it to results when it matches the query.
- **Search:** Searches the site using common search engines. The found results are downloaded and added to the results when they match the query.

Depending on your settings, promising links are followed.

TAKING OVER URLS

To take over bookmarks from other applications and create new search sets from them, use drag-and-drop or copy/paste, or import bookmarks or OPML files. Open the settings editor and use *File > Import* or the *Action* menu to import bookmarks from Camino, Firefox, OmniWeb or Safari, as well as OPML files generated by news readers or DEVONthink.

CONTEXTUAL MENU

The contextual menu allows you to work with website addresses selected in the sites list.

- **Open:** Opens the selected sites in separate web browser windows.
- **Open In Tabs:** Opens the selected sites in separate tabs in a new web browser window.
- **Launch URL:** Opens the website in your default web browser.
- **Enable/Disable:** Checks or unchecks an item. Unchecked (disabled) websites are not scanned when using this search set.
- **Copy:** Copy the URL of the selected website to the clipboard.
- **Paste:** Pastes a URL from the clipboard to the list, effectively creating a new item.
- **Delete:** Deletes a selected item.

PLUGINS TAB

The *Plugins* tab defines which plugins (interfaces to search engines) DEVONagent Pro uses when you use this search set in the search window.



PLUGIN LIST

Plugins are grouped. Expand or collapse groups by clicking the grey triangle in front of the group name, like in the Finder. Check all plugins that you want DEVONagent Pro to use for this search set; uncheck all

others. Check or uncheck a group to check or uncheck plugins contained within the group. Select a plugin to display a short description.

To find out which search engines a plugin uses to get results, use *Window > Plugins & Scanners* or see the appendix.

> **Example:** Check "Images", "Info (Pictures)" and "Picsearch (Images)" to search all major picture search engines.

RESULTS PER PLUGIN

This value defines the number of results delivered by every plugin. It limits the results pool to the most relevant <n> results. Adjust this to whatever suits your requirements; the default value is 100.

ACTIONS TAB

The *Actions* tab lets you attach additional actions to a search set that DEVONagent Pro executes after finishing a search run using this search set.



INTERFACE

- **Bounce Dock icon:** Bounces DEVONagent Pro's Dock icon once when the search run is completed.
- **Zoom and bring to front:** Zooms the search window and makes it the frontmost window.
- **Use Notifications:** Posts a notification on OS X 10.8 "Mountain Lion" or later.
- **Play sound:** Plays a sound. Select the sound to be played from the pop-up menu; all systemwide alarm sounds are available.
- **Speak text:** Speaks entered text. Use the escape sequence "%d" in the text to announce the number of found items.

RESULTS

- **Archive results:** Adds all found pages to the internal archive.
- **Add results to DEVONthink:** Adds all found pages to the currently opened DEVONthink database. Choose the desired format and destination from the popup menus below this option.
- **Send mail to:** Sends a summary of the found information to an entered email address. This is especially useful when used with a schedule.
- **Execute script:** Executes an AppleScript. Use this to do whatever you like with

the found information, e.g., feed it into a local workflow or post automatically to a website.

> Note: The email function uses the email account defined in *Preferences, Email* tab.

SCHEDULE TAB

The *Schedule* tab is what makes DEVONagent Pro a bona fide information agent. It lets you schedule automatic query runs hourly, daily or weekly, and return the results by email, archive them internally, or add them to your DEVONthink database.



> Note: A scheduled search set uses the default query you enter on the "General" tab and runs this query at the scheduled time. Make sure to enter a default query when you use the scheduler.

FREQUENCY, ...

- **Frequency:** Define if you want DEVONagent Pro to run the search set *hourly, daily,* or *weekly,* or select *Never* to switch the scheduler off.
- **Time of Day:** Define at which time of the day DEVONagent Pro runs the search set.
- **Day of Week:** Define on which day of the week DEVONagent Pro runs the search set.

OPTIONS

- **Quit when done:** Quits DEVONagent Pro after the search run is completed.
- **Close window:** Closes the search window when the search run is completed.
- **Ignore cache:** Ignores the cache and always load all pages from the Internet. Uncheck to use DEVONagent Pro's cache and to reduce network traffic.
- **Next run:** Checks when this search set will run next (informative only).

MENUS

IN THIS CHAPTER

The DEVONagent Pro menu	38
The File menu	39
The Edit menu	41
The Data menu	41
The Sort menu	43
The View menu	43
The Web menu	44
The History menu	46
The Go menu	46
The Window menu	47
The Services menu	47
The Scripts menu	48
The Help menu	48
The Dock menu	49

A complete listing of all commands DEVONagent Pro offers in the menu bar, the global *Services* menu, and the handy *Dock* menu.

THE DEVONAGENT PRO MENU

The *DEVONagent Pro* menu is similar to the application menu in any Mac application. It contains commands for displaying the splash screen, opening the preferences window,accessing the *Services* menu, hiding and showing windows, and, of course, quitting the application.

ABOUT DEVONAGENT PRO, ...

- **About DEVONagent Pro:** Shows information about DEVONagent Pro including the version number and licensing information.
- **Check for Updates:** Checks if updates for DEVONagent Pro are available. By default, DEVONagent Pro checks for updates automatically; change your update settings in the Preferences, *Update* pane.

> Note: No information from your computer is uploaded to the DEVONtechnologies server during the check for updates. DEVONagent Pro only downloads a file listing the most current versions to your Mac.

PREFERENCES, ...

- **Preferences:** Opens the *Preferences*.
- **Private Browsing:** Select this command to check or uncheck the private browsing mode. If this menu item is checked, DEVONagent Pro clears all caches, history files, and the find pasteboard after quitting, so that anyone using this user account on this computer cannot later discover your search history. This option also prevents DEVONagent Pro from storing previous search terms in the *Recent Searches* sub-menu of the magnifying glass pop-up menu of search windows.
- **Empty Cache:** Empties the disk cache that is used to speed up browsing. Use this if you are running out of disk space or when you feel that pages or elements are not up-to-date. Emptying the cache effectively forces DEVONagent Pro to download from

the Internet all files in their most recent versions.

PURCHASE, ...

- **Purchase:** Opens the DEVONtechnologies website and places DEVONagent Pro into your shopping cart. If this copy of DEVONagent Pro is already licensed, you will be presented with the choice of buying an upgrade for your existing license or buying another full license.
- **Enter License:** Use this command to enter your licence code. Make sure you enter ALL the details EXACTLY as they appear in the licence code email. It is best to use copy-and-paste for transferring name, organization, and licence code from the email message to the appropriate fields. Make sure not to highlight any spaces before or after the required information.

> Note: *Enter License* changes into *License* as soon as you enter a valid license code.

SERVICES

- The *Services* sub-menu gives you access to special commands published by other Mac applications such as TextEdit or Safari, or by services extensions such as our own WordService or CalcService. Also, DEVONagent Pro publishes its own services. See also p. 47ff

THE FILE MENU

The "File" menu contains all commands that create new windows, open or save files or settings, and print.

NEW SEARCH, ...

- **New Search:** Opens a new search window. You use search windows to send queries to a predefined search set or a selected plugin, that then queries one or multiple search engines and presents the weighted results. Search windows are what give DEVONagent Pro its name and purpose.
- **New Plugin:** Opens the *Plugins & Scanners* window and lets you create a new custom plugin. Use this function to easily create a plugin for your favorite yet-to-be search engine.

NEW BROWSER, ...

- **New Browser:** Opens a new web browser window.Use this function to use DEVONagent Pro as a standard web browser that is optimized for research. The web browser is based on the same WebKit engine used by Safari.
- **New Tab:** Creates a new tab in the frontmost web browser window.If the frontmost window is a search window rather than a web browser window, this command opens a new web browser window instead.
- **Open Location:** Brings the address field of the frontmost web browser window into focus. If no web browser window is open, DEVONagent Pro opens a new one, equal to *File > New Browser.*

OPEN FILE, ...

- **Open File:** Opens a local file for viewing in a new web browser window or in a previsouly

saved search. Alternatively, drag the file onto DEVONagent Pro's icon in the Dock.

- **Open Recent:** Lists the recently used saved searches so that you can quickly open them.

SAVE AS, ...

- **Save, Save As:** Saves the content of the frontmost web browser window in its original format or a search run for future reference. Webpages are saved as pure HTML code or webarchives (see below), images, movies, and PDFs in their respective formats. Search runs are saved as '.agentSearch' files that can be double-clicked in the Finder or opened via *File & Open*. They include the term, the used set or plugin, the settings, the results and their sortings, the digest, the log, and a Quick Look preview.

IMPORT

- **Sets:** Imports saved search setsand adds them to the list of available search sets. You also can import saved search sets by double-clicking them in the Finder or by dragging them to DEVONagent Pro's Dock icon.
- **OPML:** Imports all URLs contained in an OPML file and creates a new search setwith the URLs in the Sites tab. Use this to import RSS feeds exported as OPML from a news reader.
- **<Application> Bookmarks:** Imports Camino, Firefox, Chrome, OmniWeb, or Safari bookmarks and creates a new search set with all imported URLs in the Sites tab. Both site and news feed bookmarks are supported. If a web browser window is frontmost, the bookmarks will be added to DEVONagent Pro's own bookmark list.
- **Safari History:** Imports the Safari history file and creates a new search setwith all imported URLs in the Sites tab.

EXPORT

- **Digest:** Exports the digest as plain or rich text file. This command can also export the topics map as a PDF document or OPML for outliners and mind-mapping applications.
- **Report:** Exports a search report as PDF, CSV (comma-separated values), HTML, or OPML file. Use the CSV or OPML formats to export all results in a structured way in order to re-import them into other applications such as Microsoft Excel or Apple Numbers.
- **Results:** Exports selected search results in their original formats, or as bookmarks, plain text files or rich text files.
- **Sets:** Exports one or more selected search sets and saves them as files. These files can be re-imported using *File > Import > Sets* or by double-clicking them in the Finder. Use exported sets to shared them with other DEVONagent Pro users or between computers.

PAGE SETUP, PRINT

- **Page Setup:** Opens the standard page setup dialog.
- **Print:** Prints the contents of the frontmost window.

THE EDIT MENU

The "Edit" menu contains all commands and options related to editing. You'll find the classic Mac cut/copy/paste and find/replace commands here, as well as many more.

UNDO, REDO

- **Undo:** Takes your changes back one step. Undo mainly works for text edits, but will not bring back deleted documents.
- **Redo:** Redo re-does the last undone edit.

CUT, COPY, PASTE

- **Cut:** Cuts the selected items or text passages.
- **Copy:** Copies the selected items or text passages to the clipboard.
- **Copy URL:** Copies the URL of the selected page or frontmost web browser window to the Clipboard.
- **Paste:** Pastes whatever is on the Clipboard.
- **Clear:** Deletes the selected item or piece of text.
- **Complete:** Auto-completes a word in text and search fields as well as in text views. This OS X standard function relies on the dictionary you have selected in the spellchecker (see below).
- **Select all:** Selects all contents of the frontmost window.
- **Deselect all:** Deselects all contents of the frontmost window. Hold the ⌥Option key to show this menu item.

FIND

This sub-menu contains commands for finding and replacing text. In most ways it is similar to the *Find* command in most Mac application, but it also contains DEVONagent Pro-specific items.

- **In Internet:** Opens a new search window.
- **In Results:**
- **Find...:** Opens the standard find panel.
- **Find Next/Previous:** Jumps to the next or previous occurrence of the find term.
- **Use Selection for Find:** Copies the selected piece of text to the find clipboard or into the search field of the find panel if it is open.
- **Scroll To Selection:** Scrolls the displayed documents to the current selection.

SPELLING, ...

- **Spelling and Grammar:** The spell and grammar checker. Useful for checking text, e.g., when filling out form fields.
- **Speech:** Speaks a selected piece of text.
- **Special Characters...:** Shows the standard special characters panel for inserting characters that you cannot enter directly with your keyboard, such as accented or umlauted characters.

THE DATA MENU

The *Data* menu provides commands for opening search results, exporting them to DEVONthink, archiving them, or organzing them in the built-in archive.

NEW GROUP, ...

- **New Group:** Creates a new group in the archive. To create a sub-group, select an archive group first, then use this command.
- **Open:** Opens the selected search results in new web browser windows. Same as double-clicking the results.
- **Open In Tabs:** Opens the selected search results in separate tabs in a new web browser window.
- **Launch URL:** Opens selected search results in your default web browser. If DEVONagent Pro is your default browser, this command is equal to "Data > Open..."

ADD TO DEVONTHINK, ...

- **via Clip to DEVONthink:**
- **Resource:** Adds the selected page or document as-is to DEVONthink.
- **Bookmark:** Saves links to the selected pages as bookmarks.
- **Rich Text:** Saves selected text as a new text document.
- **Summary:** Saves the whole digest as text document. Available on the *Digest* and *Results* tabs of *Search* windows as well as in the archive.
- **Formatted Note:** Saves the selected page as new formatted note.
- **Markdown:** Saves the selected page as new Markdown document.
- **PDF (one page):** Saves the selected pages as PDFs without page breaks. A long webpage will be saved as one, very long page, making this function ideal for archiving. Only available in the web browser.
- **PDF (paginated):** Saves the selected pages as PDFs with page breaks. Use this for archiving webpages that you may want to print later.
- **Web Archive:** Saves webpages as webarchives. Webarchives are self-contained files that include one webpage that includes all additional files necessary for displaying, e.g., embedded images or movies. Only available in the web browser.

DEVONagent Pro adds 'DEVONagent Pro plus the name of the plugin used to find the page and its version to the comments when adding to DEVONthink.

> Note: These items are only available when DEVONthink is installed on your Mac.

ADD TO SET, ...

- **Add To Set:** Adds selected pages, e.g., search results, to the "Sites" listof a search setyou select from the sub-menu. These pages will be scanned for an entered query the next time you use this search set and can be useful to include in future searches. Select "New Set..." from the sub-menu to create a new search with the selected pages.
- **Add To Archive:** Adds the selected results to the archive,creating a new group for current search run. If a group for this search run already exists, any subsequently added page from same search run will be added to this archive group.
- **Add All To Archive:** Appears insteat of *Add To Archive* when you hold the ⌥Option key down. Adds all results of a search run to the archive,creating a new group for them. Use this command to archive all results of a search run with one click.

MARK ALL READ, ...

- **Mark All Read:** Marks the selected results as read or unread.
- **Delete:** Deletes search results from a results list in a search window,as well as groups or items from the archive.
- **Delete Domain:** Deletes all results from the selected domains from the current results list.
- **Delete & Exclude Domain:** Deletes the selected search results from a results list in a search window and adds the domains of the pages to the list of excluded domains. All other search results matching the exluded domains are removed. Use this function to quickly exclude an unwanted domain without having to block it via the Preferences. Alternative menu item to *Delete Domains*.
- **Clear Log:** Clears the *Log* tab of the frontmost *Search* window.

> Note: Use *Delete* and *Delete & Exclude Domain* with care. You cannot undo these commands.

THE SORT MENU

The *Sort* menu sorts search results in a variety of ways.

Unsorted, By Name, ...:

- **Unsorted:** List results in their natural order. Useful after opening a saved search to easily view new results.
- **Name:** List results sorted by name.
- **Date:** List results sorted by date.
- **Size:** List results sorted by size.
- **URL:** List results sorted by URLs.
- **Top Level Domain:** List results sorted by their top level domain.
- **Relevance:** List results sorted by relevance.
- **Number of Objects:** List results sorted by the number of found objects.

Top Level Domain means the last part of a website address. Usually it is defined by the country the website is located in, e.g., '.de' for Germany or '.cz' for the Czech Republic, or by function, such as '.com' for a world-wide commercial site or '.mil' for a US military site.

Relevance is the relevance of a result compared to all collected results in respect to the query. This is the default sorting order.

Ascending, Descending:

- **Ascending:** Sorts items ascending.
- **Descending:** Sorts items descending.

THE VIEW MENU

The *View* menu allows you to switch between the various tabs of a *Search* window, to switch Cover Flow on and off, and to customize how objects are presented in web browser windows.

DIGEST, ...

- **Digest:** Switches to the "Digest" tab. The digest shows a summary of the found information (not the pages), sorted by relevance. In addition, it visualizes topics in a topics map that lets you navigate the results graphically. Use the digest and the topics map to work with the

information itself instead of manually visiting webpages.

- **Results:** Switches to the "Pages" tab. The "Pages" tab lists all found pages, sorted by relevance (or any sorting order you choose in the "Sort"menu). A preview pane displays the relevant text parts of a selected result.
- **Log:** Switches to the "Log" tab. The log lists all webpages that DEVONagent Pro has filtered out as being irrelevant to the query or outdated. View a selected page in the preview page. Use the log to see how many pages you DON'T have to look at because you're using DEVONagent Pro instead of Google or other search engines.
- **Settings:**
- **Advanced:**

SUMMARY, OBJECTS

- **Summary:** Selects the *Summary* tab of the *Pages* tab of *Search* windows.
- **Objects:** Selects the *Objects* tab of the *Pages* tab of *Search* windows.

COVER FLOW, ...

- **Cover Flow:** Switches between the regular display of results or tabs and Cover Flow. Cover Flow lets you browse graphically and quickly through results or the pages opened in multiple browser tabs.
- **Quick Look:** Shows a Quick Look preview for the selected search result.
- **Slideshow:** Shows a slideshow for multiple selected search results. Hold the *Shift* key to show this alternative command.
- **Inverse Appearance:** Inverts the colors of the results list in search and browser windows to match it with Cover Flow. Uncheck to return to the regular black-on-white appearance.
- **Show Icon Preview:** Shows or hides the icon previews in *Results* tab of search windows, *Sidebar* drawer and *See Also* tab the Inspectors pane of web browser windows and the archive.
- **Use Small Icons:** When checked, objects are shown with small icons and more information in the sidebar of web browser windows. When unchecked, objects are shown with large icons and no details.

SHOW TOOLBAR, ...

- **Hide/Show Toolbar:** Hides or shows the toolbar of the frontmost window.
- **Customize Toolbar:** Lets you configure the toolbar of the frontmost window.
- **Enter/Exit Full Screen:** Puts the frontmost window into full screen or back into windowed mode. Press ⎋ to return to windowed mode.

THE WEB MENU

The *Web* menu contains all commands that are directly related to web browsing, from quickly turning Java on or off to switching between views and reloading a webpage. All commands in this menu act on the frontmost web browser window.

ENABLE PLUGINS, ...

- **Plugins:** Enables or disables plugins.
- **Java:** Enables or disables Java.
- **JavaScript:** Enables or disables JavaScript.

Use these options to quickly switch plugins, Java, or JavaScript on and off without visiting the *Preferences*.

STOP LOADING, ...

- **Stop Loading:** Stops loading a the webpage. This is equal to clicking the reload/stop button on the address bar of a web browser window when a page is loading.
- **Reload Page:** Reloads the webpage. This is equal to clicking the reload/stop button on the address bar of a web browser window when a page is completely loaded.
- **Actual Size:** Zooms the page to its actual size.
- **Zoom In:** Zooms in.
- **Zoom Out:** Zooms out.
- **Zoom Text Only:** When this option is checked, only the text of the page is made larger and smaller. When unchecked, DEVONagent Pro uses Safari-4-style zooming.
- **Translate:** Translates the displayed page using the Google language tools to your system's preferred language. This command is unavailable if the recognized language of the displayed page is the same as the preferred language of your system.
- **Text Encoding:** Changes the text encoding used for displaying a webpage. Use this sub-menu to manually adjust the text encoding if DEVONagent Pro displays accented characters, umlauts or East Asian characters incorrectly. Generally, websites publish their encoding and DEVONagent Pro reads this metadata for adjusting the encoding automatically.

VIEW, ...

- **Source Code:** Shows the source code of the webpage.
- **Text:** Shows only the pure text of the webpage.
- **Layout:** Shows the webpage rendered (normal).

These three options switch the mode of the frontmost web browser window between different modes. Use these modes to view only the raw text of a layout-intensive webpage, or to switch to the source code to find information that is hidden in the code but not visible in the layout. DEVONagent Pro displays the source code with syntax coloring. The text only mode is also useful for copying/extracting information from pages with a complex table layout.

SIDEBAR

- **Show:** Shows or hides the sidebar.
- **Bookmarks:** Switches to the bookmarks pane of the sidebar.
- **Results:** Switches to the results pane of the sidebar.

INSPECTORS

- **Show:** Shows or hides the *Inspectors* tab of the frontmost web browser window.
- **Properties:** Switches to the properties tab.
- **Objects:** Switches to the objects tab.
- **See Also:** Switches to the *See also* tab.

ADDRESS BAR

- **Address Bar:** Shows or hides the address bar. Hiding the address bar gives you more

useable screen space for the displayed webpage.

THE HISTORY MENU

As with any web browser, the *History* menu lists all webpages previously visited, divided into subfolders for each day, and marked with the date and time you last viewed them.

BACK, FORWARD, CLEAR HISTORY

- **Back, Forward:** Moves back and forth between the visited pages. These commands are equal to the back and forward buttons in the address bar of web browser windows. Since there is no history when private browsing is active, these commands are not available when private browsing is switched on.
- **Clear History:** Clears the history.

VISITED WEBPAGES

The rest of the *History* menu lists the previously visited webpages, sorted from the top by age.

THE GO MENU

The *Go* menu contains commands for navigating back and forth through a results list in a search window or occurrences of a search word, as well as for using and managing bookmarks.

NEXT/PREVIOUS RESULT/OCCURRENCE

- **Next/Previous Result:** Navigates back and forth through the results lists to which the displayed webpage belongs. Use these commands to go through the pages resulting from a search run.
- **Next/Previous Occurrence:** Jumps to the next or previous occurrence of the search term, e.g., in the digest or pages tabs of search windows.

BOOKMARKS

Besides the commands mentioned above, the Go menu gives you access to the bookmarks of Safari, Camino, Firefox, or OmniWeb, or DEVONagent Pro's own bookmarks list. Select which bookmarks DEVONagent Pro shows in the *Go* menu in the preferences.

- **Add:** Adds a bookmark for the currently shown webpage.
- **Add Folder:** Adds an empty folder to the bookmarks list.
- **Edit:** Opens an edit sheet for the currently selected bookmark. This function is unavailable when two or more bookmarks are selected.
- **Delete:** Deletes the selected bookmarks.
- **<Bookmarks>:** Opens any selected bookmark; use *Open in Tabs* in any bookmark folder to open all bookmarks in the folder in separate tabs.

For these commands to work, a web browser window needs to be active and DEVONagent Pro use its own bookmarks. You cannot yet edit Safari's bookmarks from within DEVONagent Pro.

BONJOUR

The Bonjour part of the *Go* menu lists web services advertised on the local network via Bonjour, e.g., printers with web interfaces or shared DEVONthink Pro Office databases.

WORKSPACES

Workspaces save the content and positions of all open windows so that you can restore them later. This is ideal if you are working with the same set of windows over and over again. Save the windows as a workspace and recall them whenever needed.

- **Add:** Saves the currently open windows as a workspace.
- **Edit:** Opens a window that allows you to edit saved workspaces. Click on a workspace name to change it, reorder it by dragging, and delete it with the . button.
- **Update:** Updates the last used workspace to the currently open windows.
- **Workspaces:** Restores to a previously saved workspace.

THE WINDOW MENU

As with any Mac application, the *Window* menu lists all open windows of DEVONagent Pro and gives you access to commands for managing them.

Window Commands:

- **Close/Zoom/Minimize:** These three commands resemble the red, yellow and green buttons of any window title bar and consequently close the window, maximize it or create an icon on the dock. No magic here.
- **Bring All to Front:** Brings all windows of DEVONagent Pro to the front.
- **<Window name>:** Brings a selected window to the front.

Tab Commands:

- **Close Tab:** Closes the current tab of the frontmost web browser window.
- **Select Next/Previous Tab:** Switches to the next or previous tab of the frontmost web browser window.

Archive ... Downloads:

- **Archive:** Opens the *Archive* window.
- **Search Sets:** Opens the *Search Sets* panel, which allows you to edit the available search sets.
- **Plugins & Scanners:** Opens the *Plugins & Scanners* panel that lists all installed plugins and scanner modules. Use this panel to see which plugins or scanner modules are available, get more information about them, and activate and deactivate them.
- **Downloads:** This command opens the *Downloads* panel. Use it to download files from the Internet to your computer.

THE SERVICES MENU

The *Application > Services* menu (where 'Application' is the name of the frontmost application) allows access to special commands published by other applications, such as TextEdit or Safari, or by services extensions such as DEVONtechnologies' WordService or CalcService. Also, DEVONagent Pro publishes its own services in the *Services* menu.



The *Services* menu is a sub-menu of every application's application menu, the menu named after the application itself and carrying the *About X*, *Hide* ... and *Quit* commands. Services usually act on a selection, e.g., selected text or files.

Services provided by DEVONagent Pro:

- **Lookup:** Opens a new search window in DEVONagent Pro with the query field pre-filled with the selected text. Use this command to quickly search for a selected piece of text.
- **Open URL:** Opens a selected piece of text as a URL in DEVONagent Pro. Use this to quickly select a URL, e.g., in an email message, and open it in a DEVONagent Pro web browser window.

Use *Application* > *Services* > *Services Preferences* to change keyboard shortcuts or hide selected commands to clean up the *Services* menu.

> Note: After installing DEVONagent Pro you may need to log out and back in again for the Finder to recognize the new *Services* menu commands and shortcuts. If one or more DEVONagent Pro *Services* menu commands does not have a keyboard shortcut assigned to them, perhaps another application grabbed it. OS X automatically assigns the correct shortcut when no other application asks for the same key combination.

THE SCRIPTS MENU

The *Scripts* menu is located left of the *Help* menu and shows a graphic AppleScript 'S' symbol instead of a normal menu title. It contains a collection of useful predefined AppleScripts you can use directly from within DEVONagent Pro.

Some of the scripts work without a selected document; others require you to select the document you want the script to interact with. In general, the script will tell you what you have to do when you select it from the *Scripts* menu.

See also p. 85ff

THE HELP MENU

The *Help* menu contains commands for opening the integrated help pages or the support assistant, or for visiting the DEVONtechnologies website.

DEVONAGENT PRO HELP

These commands open the integrated help pages that are equal to the document you reading or open the release notes.

SUPPORT ASSISTANT, TUTORIALS

Your Account: Opens your customer account page where you can look up your details and licenses.

Support Assistant: Opens the support assistant where you can, for example, read the FAQ, visit the user forum, download this documentation as printable or screen-readable PDFs, retrieve your license code, or log in to your customer account.

Tutorials: Opens the assistant on the *Tips & Tutorials* page.

Click here to open the support assistant.

> Note: If you purchased DEVONagent Pro from the Mac App Store, not all options dealing with licenses or upgrades are available.

DEVONTECHNOLOGIES

Visit the DEVONtechnologies website and ask questions or meet your fellow users in the lively user forum. Contact the DEVONtechnologies team and provide feedback directly to the development team.

You can also send a bug report including the most recent crash logs. This is an alternative menu item to *Contact us*.

THE DOCK MENU

The Dock menu appears when you ^-click or right-click DEVONagent Pro's icon in the Dock. In addition, DEVONagent Pro's icon shows a badge with the number of found results.



For all Mac applications, the Dock menu provides a selection of the commands of the application menu.

- **<Window Name>:** Brings any open window of DEVONagent Pro to the front.
- **Options > ...:** Keeps DEVONagent Pro in the Dock or removes it, adds DEVONagent Pro to your login items, or reveals the DEVONagent Pro application package in the Finder.
- **Hide:** Hides all windows of DEVONagent Pro.
- **Quit:** Quits DEVONagent Pro.

Besides these standard commands, DEVONagent Pro adds a number of its own commands to the Dock menu to make them easily accessible whenever the application is running.

- **New Search...:** Opens a new DEVONagent Pro search window. Same as *File > New Search*
- **New Browser...:** Opens a new DEVONagent Pro web browser window. Same as *File > New Browser"*
- **Bookmarks, Bonjour, Workspaces:** Gives you access to your bookmarks, depending on your settings in *Preferences > Bookmarks*, Bonjour services, and workspaces. Equals the Bookmarks, Bonjour, and Workspaces parts of the *Go* menu.

WINDOWS AND PANELS

IN THIS CHAPTER

Search window 52
Web browser 59
Archive window 66
Search sets 68
Plugins and scanners 68
Downloads 71
Preferences 72
Assistant 72

DEVONagent Pro uses a number of different windows for running search queries, displaying webpages, setting up search sets, and downloading files.

SEARCH WINDOW



The search window is where you start search runs and work with the results. You open a new search window with *File > New Search* In its minimized form, the search window consists only of an entry field for the query, a pop-up menu for selecting the search sets to be used, a *Start/Stop* button, and an *Append* button. In maximized form, it is divided into four tabs: *Digest*, *Results*, *Log*, and *Settings*. You can switch between minimized and maximized form by clicking the green window gadget. Also, you can choose whether you want to open new search windows as either minimized or maximized in the preferences, "General" tab.

To start a search run, select the correct search set from the magnifier pop-up menu in the entry field, enter your query and click the *Start* button. DEVONagent Pro then queries all search engines and scans all webpages defined by the search set. As soon as the search run has finished (or you have clicked the *Stop* button), DEVONagent Pro expands the search window, if necessary, and presents the results in either the *Digest* or the *Results* tab, depending on your preferences.

If you have already performed a search run, you can also use the *Append* button instead of *Start* to append the search results to the previously collected ones instead of replacing them.

> Note: DEVONagent Pro limits search runs to 500.000 result pages and 32 GB of data. This prevents flooding your hard disk when your search query or your *Follow Links* settings are too broad.

MAGNIFYING GLASS POP-UP MENU

The magnifying glass pop-up menu lets you select the search set you want to use for your search. For a general search, use the

search set *Web (Fast)*. You can define your own search sets in the *Search Sets* window, which you can open by selecting *Edit Search Sets* from the magnifier pop-up menu.

User-defined plugins are listed in bold.

> Note: You can easily create a new search set by using the + button left of the search term field. Use this to run the same query with exactly the same settings again in the future.

Plugins: In addition, this pop-up menu gives you direct access to every installed plugin. This way, you don't have to define a search set just for querying a special search engine once. You can simply pick the one you want to use, enter the query and hit the *Start* button. Tool tips give you more information about each plugin.

Recent searches: The magnifying glass pop-up remembers the last 25 search terms (when private browsing is not enabled). You recall the terms simply by selecting them from the *Recent Searches* part of the menu. Remember to select the correct search set or plugin. Clearing the recent serarches empties the system-wide find pasteboard too.

Recently used: Finally, find here the most recently used plugins or search sets for quick access.

STATUS BAR

The status bar below the search field shows information about the number and size of the downloaded files, found results and objects, as well as unread results.

DIGEST TAB

DEVONagent Pro's search window is divided into three views, each presenting different aspects of the information that has been collected in a search run. You switch between the views by clicking the tabs separating the search field from the rest of the window.

The digest differs from what traditional search engines and applications display. This is what makes DEVONagent Pro unique. Instead of simply listing the URLs of found pages, the digest shows a list of topic words and two- and three-word expressions that DEVONagent Pro has extracted from the collected data. This list not only includes the entered search words, but also many other words that the artifical intelligence core of DEVONagent Pro found to be important and related to the query. You can sort this list by topic or relevance by clicking the column headers. The number of sentences with occurences is shown for each topic word.



Topics map: In the right-hand side pane, DEVONagent Pro shows short paragraphs from every found webpage until you select one or more topic words. DEVONagent Pro shows an AI-generated visual representation of the selected topic and its relations to other topics in a mind-map style. Two-and three-word word expressions do not show a topics map; for multiple selected topic words DEVONagent Pro always picks the top one.

The selected topic becomes a big blob in the center of the map with related topics arranged around it. The larger a blob, and the more orange or red it is, the more important it is. Topics that are related to the selected word but are not part of the topics list on the left, are shown in blue. Light grey lines indicate closer relationships between topics. Move the mouse over the topic blobs to highlight the connetions to other topics in the graph; click a blob to select it. Double-click a topic in the map to make it the center of the graph. DEVONagent Pro will recalculate the map accordingly. This is similar to selecting another topic word from the list on the left.

Use the arrow buttons in the bottom bar of the topics map area to navigate back and forth through the results in the digest.

Summary: Finally, below the topics map, DEVONagent Pro shows a summary of the extracted information, sorted by relevance. At the end of each extract, you'll find a link to the original source where DEVONagent Pro extracted the data from (click the link with ⌘ held to open it on a new tab instead of in a new window). The summary delivers the actual answer to your query, effectively eliminating the need to go through a long list of links or visit hundreds of webpages manually.

The summary dynamically changes with whatever topic word or words you select in either the left-hand side pane or the topics map. This way, you can use the topics map to navigate through the found information and refocus the summary to whatever you are interested in. You can also click words in the summary with ⌥ held to refocus the topics map on the clicked word.

> Note: You can also select multiple topics with the ⇧ and ⌘ keys, or enter your own keywords separated by spaces, into the text field below the topics list. For the topics map, DEVONagent Pro will only use the first selected topic word. It does not work with words you enter into the keyword text field.

RESULTS TAB

List or Cover Flow: The *Pages* tab is similar to what most search engines deliver: a list of all found URLs including the name of the webpage and a two lines excerpt from where the search terms are found on the page. Sort the list by all the criteria that you can find in the *Sort* menu. You can also drag results to DEVONthink to quickly archive them in your database.



You can browse the results also with Cover Flow. Double-click a page in Cover Flow to open it in a new *web browser window*; hold the ⌘ key to open the new window in the background.

All pages that you haven't checked yet show a dot in front of them, similar to unread messages in Apple Mail. You can also select results and drag them to other applications, such as an open TextEdit window, DEVONthink, or the Finder, or delete pages from the list that you have found to be unrelated to your research. A badge shows the number of found scanner objects.

Preview area: In the lower pane of the *Pages* tab, DEVONagent Pro displays either a text preview of the relevant text passages for pages selected in the list above, or all objects found by the automatically applied scanners. Switch between the text preview and the objects returned by the scanners using the navigation bar above the preview.

In addition, you switch between small and large icons, download all or selected objects, and access the action menu from the navigation bar.

LOG TAB

The *Log* tab lists all pages that DEVONagent Pro has skipped.

DEVONagent Pro skipped them because they:

- Did not match the query
- Delivers an error message, e.g., the famous error 404 (file not found)
- Are an advertisement
- Are index spam created for fooling Google and other search engines

You can find a complete list of all codes used in the log in the appendix.

Effectively, the log lists all pages you did not have to look at yourself because DEVONagent Pro did that job for you.



You can sort the list by date, address, or error message by clicking the respective column headers. Click them again to reverse the sorting order. Use copy-and-paste or drag-and-drop to move or copy URLs to the *Downloads* panel, to a search set, to DEVONthink, or other applications, e.g., Safari.

SETTINGS TAB

The *Settings* tab contains some of the options from the *General* and *Advanced* of search sets and TEMPORARILY overrides these settings.



The *Settings* tabs offers the following options:

- Follow Links
- Language
- Filter & Scanner
- Secondary Query
- Search In
- Files

Use the *Settings* tab to temporarily enable or disable options, e.g., to switch on a scanner without permanently messing up the search set.

TOOLBAR

The toolbar of DEVONagent Pro's main windows carries many commands for manipulating the way it displays information and for manipulating selected items. Many of these are simply shortcuts for menu bar commands. Here's a short list of the available tools:

- **Open:** Opens the selected page(s) in a separate web browser window.
- **Launch URL:** Opens the selected page(s) in your default web browser.
- **Export:** Exports the selected page(s) as pure text, RTF(D) or HTML.
- **DEVONthink:** Adds the selected page(s) to the currently open DEVONthink database in the format you choose from the pop-up menu. Only available if DEVONthink is installed on your Mac.
- **Add:** Adds the selected page(s) to the internal archive.
- **Add All:** Adds all found pages to the internal archive.
- **Archive:** Opens a window for the internal archive.
- **Delete:** Deletes the selected page(s) from the results list.
- **Print:** Prints the results list.
- **Search:** Searches the results on the *Results* tab. Use the magnifying glass pop-up menu to adjust your search options.
- **View:** Enables or disables Cover Flow and shows or hides icon previews.

> Note: Not all of these commands are always available. You can customize the toolbar by selecting *Viiew > Customize Toolbar* or by *Control*- or right-clicking the toolbar background and selecting *Customize Toolbar* from the contextual menu.

SHORTCUTS & MODIFIER KEYS

Like any Mac application, DEVONagent Pro uses modifier keys or shortcuts to access frequently used functions or modify a standard behavior.

- **Command-click:** Adds an item to the current selection of items.
- **Shift-click:** Selects a range of items.
- **Space, Shift-Space:** Scrolls down or up in non-editable text views, e.g., the summary.

CONTEXTUAL MENU

The contextual menu, which appears when you click something with the right mouse button or when you click while holding the ^ *Control* key down, offers a range of commands tailored to what you can do with the clicked object.

Most of the commands offered by the contextual menu have counterparts in a main menu, so you'll recognize them immediately. However, to save menu bar real estate, DEVONagent Pro gives you access to some options only via the contextual menu.

- **Open:** Opens the selected pages in separate web browser windows.
- **Open In Tabs:** Opens the selected pages in separate tabs in a new web browser window.
- **Copy URL:** Copies the selected URL to the clipboard.
- **Launch URL:** Opens the selected page(s) in your default web browser.
- **Reveal in Finder:** Reveals an externally archived page in the Finder.
- **Add to DEVONthink:** Adds the pages to your currently open DEVONthinkdatabase in a variety of formats. Same as *Data > Add to DEVONthink*. Only available if DEVONthink is installed on your Mac.
- **Add to Set > ...:** Adds the addresses of the selected page(s) to the sites list of a search set.Select "New Set..." to create a new search set with the selected page(s).
- **Add to Archive:** Adds the selected page(s) to the internal archive.
- **Add All to Archive:** Adds all pages in the results list to the internal archive.
- **Export:** Exports the selected page(s).
- **Mark As Read:** Marks the selected pages as read or unread.
- **Delete:** Deletes the selected page(s) from the results list.
- **Delete Domain:** Deletes all pages from the selected domains from the results list.
- **Delete & Exclude Domain:** Deletes the selected search page(s) from the results list and adds the domain(s) of the page(s) to the list of excluded domains. Use this to quickly exclude an unwanted domain, without having to block it via the preferences.
- **Sort by > ...:** Sorts the results list by the criteria listed in the sub-menu. Alternative menu item to *Delete Domains*.
- **Clear Log:** Clears the log for the search run. Same as *Data > Clear Log*.
- **Sort By:** Sorts the results list by the selected sort key. See also p. 43ff

In text areas, e.g., the text preview on the "Pages" tab, DEVONagent Pro also offers the standard contextual menu commands for text views:

- **Search with Spotlight:** Searches for the selected text using Spotlight.
- **Search in Google:** Opens your default browser and searches for the selected text in Google.
- **Look Up in Dictionary:** Looks up the selected piece of text in the system dictionary.
- **Cut/Copy/Paste:** Same as "Edit > Cut/Copy/Paste".
- **Spelling > ...:** OS X's integrated spell checker. Choose "Spelling..." to open the spellchecker panel, and "Check Spelling" to run the spell checker on the text. "Check Spelling as You Type" is not available in read-only text views.
- **Speech > ...:** "Start Speaking" speaks selected text, "Stop Speaking" stops speaking, which is useful when speaking a very long piece of text.

WEB BROWSER

Besides being a research tool, DEVONagent Pro is a full-fledged web browser, based on the Safari engine (a.k.a. 'WebKit'). Open a new web browser window by choosing *File > New Browser*, clicking a link, or by choosing *File > Open Location* when no web browser window is frontmost.

To visit a website, enter its address into the address field of the toolbar and press ↩ or *Enter*. Alternatively, drag a URL to DEVONagent Pro's application icon in the Finder or in the Dock, or into an open browser window.

Instead of a URL, you can use keywords to directly send a simple query to a search engine. This effectively replaces the Google search field found in Safari and other browsers. The keywords are defined by the plugins, but can be edited individually. If the plugin supports it, keywords use a search engine specific to the system language. Another option is to use DuckDuckgo Bangs in the address field.

> **Example:** Enter 'google devonthink' to query Google for 'devonthink'; enter '!nws saginaw,mi' to ask the National Weather Service for the weather of Saginaw, MI.

TAB BAR

The tab bar below the toolbar lists all tabs of the web browser window. Each tab contains a different webpage. Use tabs to open multiple webpages without cluttering your screen with dozens of separate windows. Switch between tabs by simply clicking the tab you want to bring to the foreground. If all tabs do not fit into the available space, DEVONagent Pro shows an optional pop-up menu at the right-hand side of the tab bar listing all available tabs.

Point to a tab for one second without clicking to show a tooltip with a thumbnail preview of the webpage displayed on the tab. This is useful when you cannot remember which page you opened on which tab. Right- or ^Control-click a tab to show a contextual menu.

Inactive tabs show a close button instead of the webpage icon. Also, after the last tab, DEVONagent Pro shows a "+" button for creating new, empty tabs.

TOOLBAR

The toolbar of a web browser window can be customized like any other toolbar using *View > Customize Toolbar*. The following tools are available:

- **Window:** Shows or hides the sidebar; switches Cover Flow mode on and off; switches to full screen mode; hides or shows the *Inspectors* pane.
- **View:** Switches between source code, text, and layout views. Use the source code view to inspect how a page is constructed and the text mode to see the raw text without any distractions.
- **Action Menu:** Access frequently used commands directly from the toolbar. See also p. 63ff
- **Back/Forward:** Navigates back and forth through the visited pages, like a standard web browser. Similar to "History > Back/Forward".
- **Smaller/Bigger:** Makes the text smaller or bigger.
- **Reload/Stop:** Reloads the current page (circle arrow icon) or stops loading a page ('X' icon).
- **Address:** Type in the URL to load here, or type in a keyword and a simple query. Read more about keywords here. Select the whole address in the address field and drag it to other windows or applications, e.g., the Finder.
- **Translate:** Shows the language of the displayed page as recognized by DEVONagent Pro as a flag. If your system's preferred language is different, clicking the flag translates the page using Google language tools.
- **See Also:** Opens a drawer with pages similar to the current one, sorted by relevance. Select a page in the drawer to display it. The originating page is always listed on the top of the list. Use *See Also* for finding related pages in the results pool. See also p. 60ff
- **Share:** Shares the page via services like iMessage, Mail, Twitter, Facebook, and AirDrop, or adds it to Safari's Reading List.

If a bookmark for the current page exists in the open DEVONthink Pro databases, a small DEVONthink icon is shown on the right-hand side of the address field.

INSPECTORS

The *Inspectors* pane presents additional information about the displayed web page, e.g. metadata or extracted objects. Depending on the displayed page, none, one, or multiple of the following tabs, can be available:

- Properties
- See Also
- AppleScript scripts
- Audio

- Code
- Downloadable archives
- Electronic business cards (.vcard)
- Email addresses
- Twitter posts
- Images
- LaTeX files
- Links
- News feed (Atom, RSS, JSON)
- Office documents
- Spreadsheet documents
- Thumbnail galleries
- Cooking recipes
- Video (live)
- Videos
- Wallpapers, desktop pictures
- Webcams

Properties tab: The Properties tab shows metadata about the displayed web page.

See Also tab: The See Also tab lists other pages related to the displayed page from three sources:

- **Search:** The results of the search run to which the page belongs.
- **Archive:** Pages in the internal archive.
- **DEVONthink Pro:** The currently open DEVONthink databases.
- **Web:** Related pages from the Web, either provided by plugins or common search engines.

Click any item in the pane to display it; double-clicking opens it in a new tab or window. The original page stays at the top of the list so that you can easily go back to it. Results from DEVONthink that have a URL associated with them are also shown with a single click; results without URLs open in DEVONthink on a double-click.

Objects: Which, if any, of the other above tabs are available depends on the web page shown in the window. DEVONagent Pro collects all objects from the page using the available scanners and lists them in separate tabs in the sidebar. Click any found object to display it (double-click to open it in a new tab, if tabbed browsing is enabled, or a new browser window). Click with ⌘ pressed to open the result in a new tab. The *Back* button brings you back to the original page.

Botttom bar: The bar at the bottom of the sidebar gives you access to commonly used commands, depending on which tab is active.

- **List:** Shows objects in a list with small icons. See also p. 44ff
- **Icons:** Shows objects as large icons. See also p. 44ff
- **Download:** Adds the selected objects to the *Download Manager*. If no item is selected all items will be added.
- **Action:** Gives access to the same options as the contextual menu (see below).

Contextual menu: The contextual menu gives you direct access to commands acting on the selected items. Commands are only available when applicable.

- **Open in New Window:** Opens the selected items in a new web browser window.
- **Open in New Tab:** Opens the selected items in a new tab.
- **Open in PhotoStickies:** Opens a selected items in PhotoStickies.

- **Open in DEVONthink:** Opens a document located in DEVONthink.
- **Reveal in DEVONthink:** Reveals a document located in DEVONthink.
- **Add Link to DEVONthink:** Adds a link to the result to DEVONthink.
- **Copy:** Copies the selected items to the clipboard.
- **Download:** Downloads the selected items (or the items referred to by links).
- **Select/Deselect All:** Selects or deselects all items in the list.
- **Use Small Icons:** When checked (default), DEVONagent Pro displays small icons in the drawer, including the name and the link to or of the item; when unchecked, it displays large icons, 160 pixels wide, and shows no links.
- **Open Video in Tab:** Opens an HTML 5 video in a new tab.
- **Open Video in New Window:** Opens an HTML 5 video in a new window
- **Download Video:** Downloads an HTML 5 video.

SIDEBAR

The sidebar is the place in a web browser window where all additional information is presented, from bookmarks to the list of search results (if the page is part of the results of a current search run) to extracted objects. The sidebar is divided into several sub-tabs:

- Bookmarks
- Results

Bookmarks: Use the Preferences to choose what bookmarks and additional elements, e.g., Web servers announced via Bonjour, DEVONthink Pro bookmarks, or workspaces, are listed on the *Bookmarks* pane. If you are using DEVONagent Pro for your bookmark management, use cut/copy/paste, drag-and-drop, or the contextual menu (see below) to edit your bookmarks.

Results: The *Results* pane lists all results of the search run that the shown webpage belongs to. This pane is unavailable if the page does not belong to a currently open search run.

Bottom bar: The bar at the bottom of the sidebar gives you access to commonly used commands, depending on which tab is active.

- **+:** Adds the current page to the bookmarks.
- **-:** Removes the current page from the bookmarks.
- **Back:** Selects the previous search results from the current results set.
- **Forward:** Selects the next search results from the current results set.
- **Delete:** Deletes the current page from the current results set.
- **Action:** Gives access to the same options as the contextual menu (see below).

Contextual menu: The contextual menu gives you direct access to commands acting on the selected items. Commands are only available when applicable.

- **Next/previous result:** Navigates back and forth through the list of results. Same as *Go > Next/Previous Result*.
- **Mark as Read/Unread:** Marks the selected results as read/unread.
- **Delete:** Deletes the result from the results of the search run it was opened from.

- **Delete & Exclude Domain:** Deletes the result from the results of the search run it was opened from and adds it to the exclude list in the Preferences.
- **Sort:** Changes the sorting of the result list.
- **Cut:** Copies the selected items to the clipboard and removes it from the list.
- **Copy:** Copies the selected items to the clipboard.
- **Paste:** Pastes bookmarks on the clipboard.
- **Add Bookmark:** Adds the current page to the bookmarks.
- **Add Bookmark Folder:** Adds a new folder to the bookmarks.
- **Import:** Imports bookmarks. See also p. 40ff
- **Edit:** Opens an editing sheet for the selected bookmark.
- **Delete:** Deletes the selected items.
- **Show Icon Preview:** When checked, DEVONagent Pro shows a preview icon for bookmarks.

- **Add Link to DEVONthink:** Adds the link of the selected items to the currently open DEVONthink database. Only available if DEVONthink is installed on your Mac.
- **Copy Link:** Copies the selected links to the clipboard.

ACTION MENU

The action menu (labeled with a gear icon) makes frequently used commands conveniently accessible from the toolbar.

- **Copy URL:** Copies the address of the current page to the Clipboard.
- **Launch URL:** Opens the selected pages in your default web browser.
- **Add to DEVONthink:** Adds the pages to your currently open DEVONthinkdatabase in a variety of formats. Same as *Data > Add to DEVONthink*. Only available if DEVONthink is installed on your Mac.
- **Add to Set > ...:** Adds the URL of the page to the "Sites" tabof the search set you select from the sub-menu. Select "New Set..." to create a new search set with the selected page(s).
- **Add to Archive:** Adds the page to the internal archive.
- **Save As:** Saves the the selected pages as pure text, RTF(D) or HTML.
- **Translate:** Translates the displayed page using the Google language tools to your system's preferred language. This command is unavailable if the recognized language of the displayed page is the same as the preferred language of your system.
- **Inverse Appearance:** Inverts the colors of the results list to match it with Cover Flow. Uncheck to return to regular black-on-white appearance.

SHORTCUTS & MODIFIER KEYS

- **Command-click:** Opens a link or an item in the objects drawer in a new tab, if tabbed browsingis enabled. Otherwise, ⌘-click opens the clicked link in a new window.
- **Option-click:** Downloads an item on a webpage, a linked item or an item in the objects drawer via the download manager.
- **Space, Shift-Space:** Scrolls down or up in non-editable text views, e.g., the source code or text-only view.

CONTEXTUAL MENU

The contextual menu, which appears when you click something with the right mouse button or when you click while holding the ^ *Control* key down, offers a range of commands tailored to what you can do with the clicked object, for example a text passage.

Most of the commands offered by the contextual menu have counterparts in a main menu, so you'll recognize them immediately. However, to save menu bar real estate, DEVONagent Pro gives you access to some options only via the contextual menu.

- **Back/Forward:** Navigates back and forth through previously visited pages, similar to the *Back* and *Forward* toolbar buttons or *History > Back/Forward*.
- **Reload:** Reload the item or page.
- **Search in Spotlight:** Searches selected text with Spotlight.
- **See Related Text:** Opens the inspector with archived results related to the selected text passage.
- **Look Up in Dictionary:** Looks up selected text in the system dictionary.
- **Stop Loading:** Stops loading the item or page.
- **Open Image in New Window:** Opens the selected image in a new web browser window.
- **Open Image in New Tab:** Opens the selected image in a new tab of the current web browser window.
- **Open Image in PhotoStickies:** Opens the selected image in PhotoStickies.
- **Copy Image:** Copies the selected image to the clipboard.
- **Copy Image Address:** Copies the address or the selected image to the clipboard.
- **Add Image to DEVONthink:** Adds the selected image to the currently open DEVONthink database. Only available if DEVONthink is installed on your Mac.
- **Add Image to Archive:** Adds the selected image to the archive.
- **Save Image As...:** Saves the selected image to your computer.
- **Save Image to Downloads:** Saves the selected image to the default download folder.
- **Use Image as Desktop Picture:** Saves the selected image and sets it as the desktop picture.
- **Open Link in New Window:** Opens the selected link in a new web browser window.
- **Open Link in New Tab:** Opens the selected link in a new tab.
- **Open Link in PhotoStickies:** Opens the selected link in PhotoStickies.
- **Copy Link:** Copies the selected link to the clipboard.
- **Download Linked File:** Downloads the file referred to by the selected link via the Download Manager.
- **Share:** Shares the selected item using OS X's standard share mechanism (requires at least OS X Mountain Lion).
- **Add Selection to DEVONthink:** Adds the selected text to the currently open DEVONthinkdatabase. Only available if DEVONthink is installed on your Mac.
- **Add Link to DEVONthink:** Adds the selected link to the currently open DEVONthinkdatabase. Only available if DEVONthink is installed on your Mac.
- **Add Link to Set > ...:** Adds the selected link to the sites list of a search set.

- **Add PDF to DEVONthink:** Adds the displayed PDF to the currently open DEVONthink database. Only available if DEVONthink is installed on your Mac.
- **Add page address to DEVONthink:** Adds the address of the page to the currently open DEVONthink database. Only available if DEVONthink is installed on your Mac.
- **Add frame address to DEVONthink:** Adds the address of the selected frame to the currently open DEVONthink database. Only available if DEVONthink is installed on your Mac.
- **Remember Selection:** Remembers the current selection and re-applies it when you open the same page again.
- **Forget Selection:** Forgets the last saved selection.

If the WebKit developer extras are enabled more options are available.

When you ^-click or right-click the background of the page instead of a item, additional options can be available:

- **Open Page/Frame in New Window:** Opens the page or frame in a new web browser window.
- **Open Page in New Tab:** Opens the page in a new tab.
- **Copy Page/Frame Address:** Copies the address of the page or frame to the Clipboard.
- **Add Page/Frame to Archive:** Adds the page or frame to the internal archive.
- **Add Page to DEVONthink (Pro):** Adds the HTML code of the page to the currently open DEVONthink (Pro)database. Only available if DEVONthink is installed on your Mac.
- **Add Web Archive to DEVONthink (Pro):** Adds an webarchive (including all embedded images needed for correctly displaying it) of the page to the currently open DEVONthink (Pro)database. Only available if DEVONthink is installed on your Mac.
- **Add Page/Frame to Set > ...:** Adds the page or frame address to the sites list of a search set.
- **Add All Links to Set > ...:** Adds all links found on the page to the sites list of a search set.

For PDF pages, different options become available:

- **Add PDF to DEVONthink:** Adds the PDF to the currently open DEVONthinkdatabase. Only available if DEVONthink is installed on your Mac.
- **Open with Preview:** Opens the PDF in Preview.
- **Automatically Resize:** When checked, the zoom factor adjusts to the width resp. height of the browser window.
- **Zoom Out, Zoom In, Actual Size:** Zooms in or out of the document, or displays it in its actual size.
- **Single Page, ...:** Displays the PDF as single or double pages and either page by page (use the 'Next Page' and 'Previous Page' to skim through the pages forward and backwards) or continously.
- **Next Page, Previous Page:** Skims through the pages forwards or backwards.

On the *Results* pane of the sidebar, the following additional options are available:

- **Mark As Read:** Marks the selected pages as read or unread.

ARCHIVE WINDOW



The integrated archive is where you can store found pages for later reference. Open the *Archive* window with *Window > Archive*.

The archive resembles the three panes view of Apple Mail or DEVONthink: The left pane shows a list of groups, the right top pane displays page titles and URLs in a selected group, and the right bottom pane displays textual information related to the query that was used for finding a selected page. A search field in the toolbar allows you to search the archive by content, name or URL.

GROUPS

All archived pages are stored in groups. Groups are automatically created when you archive pages from the search window and are named after the search query. You can change group names at any time, delete groups or manually create new ones. You can also create sub-groups by selecting a group and then creating a new one. The number of items contained in a group is shown as a badge.

> Note: Pages not related to a previous search run are archived in sub-groups of a top-level group named 'Incoming'. The sub-groups are named with the current date.

Create new groups by using the toolbar, the contextual menu or *Data > New Group*. Rename a group by clicking it once and waiting a second (like the Finder), or by selecting it and pressing the ↩ or *Enter* key. Delete a group by selecting it and pressing *Backspace*, using the toolbar, the contextual menu or *Data > Delete*. To make a group a sub-group, drag it with the mouse or use the contextual menu.

Sort the groups by name or date with *Sort > by Name* or *Sort > by Date*. Reverse the sorting order with *Sort > Ascending/ Descending*.

PAGES

Like DEVONthink or Apple Mail, DEVONagent Pro shows the pages filed in a group when you select the group in the left pane. Select

a page and DEVONagent Pro also shows a text preview in the lower right pane with the original search words highlighted.

Rename a page by single-clicking it and waiting a second (like the Finder), or by selecting it and pressing the ↩ or *Enter* key. Delete an item by selecting it and pressing *Backspace*, using the toolbar, the contextual menu or *Data > Delete*. To move an item to another group, drag it or use the contextual menu. Items can also be dragged to DEVONthink.

To sort the pages list, click the relevant (first), title, URL or date column header. Click again to reverse the sorting order. The relevance column is only used when you search the archive using the toolbar search field.

TOOLBAR

The toolbar of DEVONagent Pro archive windows carries many commands for manipulating the way it displays information and for manipulating selected items. Many of them are simply shortcuts for menu bar commands. Here's a short list of the available tools:

- **Group +:** Adds new groups to the archive. To create a sub-group, select the parent-to-be group first, then use this tool.
- **Open:** Opens the selected page(s) in a separate web browser window.
- **Launch URL:** Opens the selected page(s) in your default web browser.
- **Export:** Exports the selected page(s) as pure text, RTF(D) or HTML.
- **DEVONthink (Pro):** Adds the selected page(s) to the currently open DEVONthink (Pro) database. Only available if DEVONthink is installed on your Mac.
- **DEVONthink (Pro) pop-up:** Adds the selected page(s) to the currently open DEVONthink (Pro) database, but allows you to select as HTML code or as a link via a pop-up menu. Only available if DEVONthink is installed on your Mac.
- **Delete:** Deletes the selected page(s) from the results list.
- **Search:** Searches the archive for entered text. Select whether you want to search the contents, the names or the URLs of the stored pages with the magnifying glass pop-up menu. Also choose whether to ignore diacritics or to search fuzzy. This search field also supports all operators and wildcards.
- **Print:** Prints the results list.

> Note: Not all of these commands are always available. You can customize the toolbar by selecting *View > Customize Toolbar* or by ^-clicking or right-clicking the toolbar background and selecting *Customize Toolbar* from the contextual menu.

SHORTCUTS & MODIFIER KEYS

Like any Mac application, DEVONagent Pro uses modifier keys or shortcuts to quickly access frequently used functions or modify a standard behavior.

- **Command-click:** Adds an item to the current selection of items.
- **Shift-click:** Selects a range of items.

CONTEXTUAL MENU

The contextual menu, which appears when you click something with the right mouse button or when you click while holding the ^ *Control* key down, offers a range of commands tailored for what you can do with the clicked object.

Most of the commands offered by the contextual menu have counterparts in a main menu, so you'll recognize them immediately. However, to save menu bar real estate, DEVONagent Pro gives you access to some options only via the contextual menu.

- **New Group:** Adds a new group to the archive. To create a sub-group, select the parent-to-be group first, then use this command. (Only available in the left pane)
- **Open:** Opens the selected pages in separate web browser windows.
- **Open In Tabs:** Opens the selected pages in separate tabs in a new web browser window.
- **Launch URL:** Opens the selected pages in your default web browser.
- **Copy URL:** Copies the selected URL to the clipboard.
- **Reveal in Finder:** Reveals an externally archived page in the Finder.
- **Add to DEVONthink:** Adds the selected pages to DEVONthink. Only available if DEVONthink is installed on your Mac.
- **Add to Set...:** Adds the URLs of selected pages to the sites list of a search set so that it will get scanned when you use that search set in the future.
- **Move To > ...:** Moves the item to the group you select from the sub-menu.
- **Export:** Exports the selected pages.
- **Delete:** Deletes the selected pages from the results list.
- **Delete Domain:** Deletes all pages from the selected domains from the result list.
- **Delete & Exclude Domain:** Deletes the selected search pages from the results list and adds the domains of the pages to the list of excluded domains. Use this to quickly exclude an unwanted domain without having to block it via the preferences. Alternative menu item to *Delete Domains*.
- **Sort by > ...:** Sorts the results list by the criteria listed in the sub-menu.

SEARCH SETS

The *Search Set* window is available via *Window > Search Sets*. Use it to modify the existing search sets or to create new ones specifically tailored for your needs.

Because search sets are so important, we have created a separate chapter about the search sets and the search sets editor. See also p. 29ff

PLUGINS AND SCANNERS

The *Plugins & Scanners* panel, available via *Window > Plugins & Scanners*, lists all installed plugins and scanners and shows additional information about them, e.g., their type, version and purpose. In addition, it allows you to create new plugins for your favorite websites and search engines.



Also, you can enable or disable plugins or whole groups of plugins by checking or unchecking them. Use this to simplify the magnifying glass pop-up menu in the search window or the plugin list in the Search Sets window.

PLUGINS & SCANNERS

All plugins and scanners are arranged in groups. Click the grey triangle in front of a group to expand it; click it again to close it. Select a plugin or scanner to show additional information:

- **Name:** Plugin name.
- **Info:** Additional information, e.g., copyright.
- **Identifier:** Internal and identification string.
- **Keywords:** Shortcuts for the plugin. See also p. 69ff
- **Description:** Textual description of the plugin.
- **Operators:** List of supported operators. For plugins that you created yourself, you can check and uncheck them to adjust which operators are supported by the search engine.

Name, info, identifier, description, and keywords of self-made XML plugins can be edited. User-defined plugins, as well as the groups *Browser*, *DEVONsphere*, and *Scanner* are shown in bold.

> Note: The group hierarchy is predefined and cannot be manually altered. If you have installed your own plugins, they appear in the top level of the hierarchy or are mirrored-in following the folder structure in '~/Library/Application Support/DEVONagent/Plugins/'.

KEYWORDS

Keywords are shortcuts that you can use to query the search engines defined by the plugin from the address bar of a web browser window.

> **Example:** The Bing plugin comes with the predefined keyword 'bing'. To send a query to Bing, type e.g., 'bing devonthink' into the address bar of a DEVONagent Pro web browser window and press ↩ or *Enter*.

This effectively replaces the search engine field that is found in other web browsers, such as Safari, with a far more flexible approach. You can add your own keyword(s) to most plugins, separated by spaces, to make them quickly accessable from any open DEVONagent Pro browser window.

In addition, the plugin's name is automatically used as a keyword.

CREATING & TESTING

Using DEVONagent Pro's built-in plugin assistant, you can easily create your own XML-based search plugin for your favorite

search engine. To create your own plugin, choose *File > New Plugin* or use the *New* toolbar icon.

In the sheet enter:

- Name for the plugin
- Short description
- Website or search engine URL

To get the URL for your search engine, run a search in your web browser, copy the URL, and paste it into the URL field of the to-be-created plugin. Then look for the URL parameter that transports the query, e.g., something like '&query=xxx'. Replace 'xxx' with '_agentQuery_'. This tells DEVONagent Pro where to enter the search term. The '_agentNumber_' and '_agentOffset_' placeholders are automatically inserted if necessary and possible. See also p. 89ff

Alternatively, if you want to create a plugin that simply searches a website, enter just the URL of the website. DEVONagent Pro will use standard search engines such as Google to run a site-specific search when you use this plugin.

DEVONagent Pro selects the *Website* or *Search Engine* radio buttons automatically, depending on the entered URL.

To test a build-in or self-created plugin use the *Test* toolbar icon. DEVONagent Pro will send 'Test' as the standard search term to the plugin and present you with the list of returned pages. Double-click results to view them in a new web browser window. Only XML and JSON plugins using 'EngineUrl' can be tested since testing XML and JSON plugins using 'EngineSite' is unnecessary.

To edit an existing XML- or JSON-based plugin, double-click it or use the *Edit* toolbar icon. DEVONagent Pro shows an XML text editor with error checking that allows you directly edit the source code of the plugin. Switch between XML and JSON format using the button at the bottom of the editing sheet. See also p. 89ff

TOOLBAR

The toolbar of the *Plugins & Scanners* windows lets you easily create new plugins, edit, test, and delete them.

- **New:** Opens a sheet for creating a new XML-based plugin.
- **Edit:** Opens a sheet for editing the XML code of the selected plugin.
- **Test:** Runs a test on the selected plugin and displays the results.
- **Delete:** Deletes the selected plugins. Built-in plugins cannot be deleted.
- **Show In Finder:** Opens a new Finder window for the folder containing the selected plugin.

CONTEXTUAL MENU

The contextual menu, which appears when you click something with the right mouse button or when you click while holding the ^ *Control* key down, offers a range of commands tailored for what you can do with the clicked object, forexample a text passage.

- **New:** Opens a sheet for creating a new XML-based plugin.
- **Edit:** Opens a sheet for editing the XML code of the selected plugin.
- **Duplicate:** Duplicates the selected plugins.

- **Show In Finder:** Opens a new Finder window for the folder containing the selected plugin.
- **Test:** Runs a test on the selected plugin and displays the results.
- **Delete:** Deletes the selected plugins. Built-in plugins cannot be deleted.

The test sheet also presents the following options in the contuextual menu:

- **Open:** Opens the selected URLs in DEVONagent Pro's built-in web browser.
- **Open In Tabs:** Opens the selected URLs in separate tabs in DEVONagent Pro's built-in web browser.
- **Launch URL:** Opens the selected URLs in the default application for their types.
- **Exclude URL:** Adds the selected URLs to the plugin's internal exclude list. Use *Retry* to re-run the test after exluding a URL.
- **Exclude Domain:** Adds the domains of the selected URLs to the plugin's internal exclude list. Use *Retry* to re-run the test after exluding a domain.
- **Include URL:** Adds the URL to the "LinksMatching" key.
- **Include Domain:** Adds the domain to the "LinksMatching" key.
- **Copy:** Copies the selected URLs to the clipboard.

DOWNLOADS

Window > Downloads opens the *Downloads* window. Use it to download files from the Internet to your computer. The download URL is automatically placed into the Finder comment of the downloaded file, as well as in the 'kMDItemWhereFroms' extended file system attribute.



For URLs that require authentication, DEVONagent Pro asks for a username and password. It also uses the systemwide cookies, and can start and stop downloads at any time.

ADDING, RESUMING, RETRYING

To add files to the Download Manager, drag a link to the item from any DEVONagent Pro web browser window or any other application to the Download Manager window, paste a copied URL or ^-click a link in a DEVONagent Pro web browser window and choose "Add to Download Manager". ⌥-clicking links in the web browser or the objects drawer adds items to the Download Manager, too. Also, DEVONagent Pro automatically puts files it cannot display into the Download Manager, if you double-click them, e.g., .zip archive files.

DEVONagent Pro downloads files added to the Download Manager immediately. To remove a file, select it and click the - button at the bottom of the window. To temporarily prevent an item from being downloaded, uncheck the checkbox in front of it. Check the checkbox to download the item. Use this to add items to the download queue, but download them later.

To resume or retry a failed download, select the file and click the back arrow button. Use the start/stop button (resembles the start/pause button of a VCR or tape player), to start or stop the entire queue.

You can also drag items from the Download Manager to other windows or to the Finder, or copy it to the Clipboard. Drag-and-drop will send the URL of the item to the target window or application.

DEVONagent Pro puts the web address where the file was downloaded from into the Spotlight comments of the file (not available if DEVONagent Pro was purchased in the Mac App Store).

ACTION MENU

The action menu provides the same options as the contextual menu.

CONTEXTUAL MENU

The contextual menu, which appears when you click something with the right mouse button or when you click while holding the ^ *Control* key down, offers a range of commands tailored to what you can do with the clicked object.

- **Cut:** Copies the selected link to the Clipboard and removes it from the queue.
- **Copy:** Copies the selected link to the Clipboard.
- **Paste:** Adds a link that is copied to Clipboard to the download manager queue.
- **Retry:** Retries a stopped or stalled download.
- **Show In Finder:** Opens a Finder window for the enclosing folders of the selected items.
- **Enable/Disable:** Enables or disables the selected item(s). Disabled (unchecked) items are not downloaded but kept in the download queue.
- **Reload:** Reloads the selected items.
- **Remove:** Removes the selected items from the queue.
- **Start/Stop Queue:** Starts or stops the download queue.
- **Purge Queue:** Purges all completed items from the queue.
- **Automatically Purge Queue:** When checked, completed items are automatically purged from the queue.

PREFERENCES

The *Preferences* window is available via DEVONagent Pro > Preferences. It contains all available options that you can modify to adapt DEVONagent Pro to your personal needs.

Because the preferences are so important, we have created a chapter just for them. See also p. 75ff

ASSISTANT

The integrated *Assistant* combines a welcome screen with tips, tricks, and tutorials, installable extras, and a suppport page that guides you through the available support options.

Click here to directly open the assistant.



WELCOME

This screen welcomes you when you start DEVONagent Pro for the very first time. It offers:

- The option to subscribe to the free DEVONtechnologies newsletter
- The tip of the day
- The extra of the day

You can access all other screens of the assistant from here, too.

GET SUPPORT

The support screen guides you through the three common steps for troubleshooting DEVONagent Pro. In addition you can have your license code resent, request a trial extension, update your details in DEVONtechnologies' customer database, or buy an upgrade or a second license.

TIPS AND TUTORIALS

Here you can always find the latest tips sand tutorials that help you squeeze the best out of DEVONagent Pro. Tutorials can be slideshows describing basic tasks in DEVONagent Pro or videos (as they become available).

Both tips and tutorials are updated live from DEVONtechnologies' server, so it's a good idea to check back from time to time. The latest tip or tutorial is always mentioned on the welcome screen.

INSTALL EXTRAS



On the extras screen, DEVONagent Pro lists available extras that you can download and install from DEVONtechnologies' server:

- Scripts
- Plugins
- Search Sets

Browse the list of extras and install them with the *Install* button. The last line of the description shows where in the *Scripts* menu or *Plugins* hierarchy the extra will show up after installation. Remove installed extras with the *Remove* button. Check *Install and update extras automatically* to receive all new extras and have them updated without visiting the window regularly yourself.

The extras are updated live from DEVONtechnologies' server so it's a good idea to check back from time to time. The latest extra is always mentioned on the welcome screen.

> Note: If one of these categories does not show up in your copy of DEVONagent Pro, there may not be extras of this type available yet for DEVONagent Pro.

PREFERENCES

IN THIS CHAPTER

General	75
Search	77
Menu extra	78
Web	79
Tabs	81
Bookmarks	81
Email	82
Update	82

The preferences window, which you open by selecting *Preferences* in the DEVONagent Pro menu, is the place where you change all global settings of DEVONagent Pro. Click here to open the *Preferences* window.

For your convenience, the preference panel is divided into tabs, just like *System preferences*. Use the icons at the top of the preferences window to select the tab you want to check or modify.

GENERAL



This tab contains all options modifying the user interface and the summarization of search results.

INTERFACE

These options define some parts of DEVONagent Pro's visual appearance.

- **Highlight occurences in HTML pages:** Check to highlight occurences of search words in web browser windowsor views.
- **Automatically zoom search panel:** Check to open new search windowssimplified.
- **Floating simplified search panel:** Makes the simplified search windowfloat above all other windows. Use this to have the search window always handy.
- **Alternating rows colors in views:** When checked, DEVONagent Pro colors lines in lists differently to make them easier to read.

ALERTS

Click *Reset* to make DEVONagent Pro show alerts again that you previously dismissed with "Don't show again" checked.

SEARCH PANEL

This option defines which tab DEVONagent Pro shows when a search run is done.

- **Digest:** Switches to the *Digest* tab when DEVONagent Pro has finished a search run.
- **Results:** Switches to the *Results* tab when DEVONagent Pro has finished a search run.
- **Log:** Switches to the *Log* tab when DEVONagent Pro has finished a search run.
- **Settings:** Switches to the *Settings* tab when DEVONagent Pro has finished a search run.

SUMMARIZATION

These options define how DEVONagent Pro creates summaries.

- **Based on sentences:** Creates summaries based on sentences. These are generally shorter summaries, so you may miss information that DEVONagent Pro classifies as not important.
- **Based on paragraphs:** Creates summaries based on whole paragraphs. These are longer summaries that are not clipped.

STARTUP

These options let you define what DEVONagent Pro does when you open it.

- **Open new query:** Opens a new, empty search window when you open DEVONagent Pro.
- **Open new browser:** Opens a new web browser window when you open DEVONagent Pro.
- **Open browsers that were open on quit:** Opens the web browser windows that were open on quit.
- **Do nothing:** Does nothing when you open DEVONagent Pro.

HOME PAGE, ...

These options define the default home page and the folder for downloaded files.

- **Home page:** Sets the home page that is loaded automatically each time you open a new web browser window.
- **Save downloaded files to:** Sets the folder into which DEVONagent Pro saves downloaded files. See also p. 71ff

FONTS

Define the fonts you want to use for searching and reading texts. Click the *Select* buttons to open the standard font panel. Hold the ⌥ Option key to reveal options for resetting the fonts to the defaults.

- **Source font:** Changes the font used for displaying source code. A monospaced font, such as Courier or Monaco, gives you the best results.
- **Text font:** Changes the font used for displaying plain text, e.g., text extracted from webpages.

SEARCH

Contains all options dealing with the cache, the number of connections, and domains excluded from searching.



GENERAL

- **Ignore instructions for robots:** Ignores instructions embedded into the HTML code of webpages that tell robots (like DEVONagent Pro) to not index a page. If unchecked (default setting), DEVONagent Pro tries to honor the wishes of the webpages creator.
- **Cache downloaded pages:** Check if you want DEVONagent Pro to store downloaded pages in its cache. This consumes disk space, but leads to much faster searches when DEVONagent Pro scans an already cached page.
- **Clear on quit:** When checked, DEVONagent Pro clears the cache upon quit.
- **Cache Directory:** Shows the path to the folder used by DEVONagent Pro for its cache. Double-click an item to reveal it in the Finder or select another folder for DEVONagent Pro to use.

CREATE PREVIEWS

Choose whether DEVONagent Pro should create previews of visited or found pages immediately or on demand, and set how DEVONagent Pro generates thumbnails of webpages.

- **Immediately:** Previews are created and cached immediately.
- **On demand:** Previews are created and cached only when needed (default).
- **Directly:** DEVONagent Pro generates thumbnails itself (higher quality).
- **Via DEVONtechnologies.com:** Generates web page thumbnails via web service (faster).

> Note: DEVONagent Pro never sends more than just the URLs of the to-be-thumbnailed webpages to Thumbshots.com.

MAX. CONNECTIONS

Use this parameter to adjust the number of connections DEVONagent Pro uses concurrently so as to match the speed of your Internet connection and your computer.

MAX. DOWNLOAD SIZE

Choose how large files can be that DEVONagent Pro downloads in search runs. Adjust this to your Internet connection speed. Files skipped due to file size are marked as "Too big" in the log tab of the search window.

EXCLUDE DOMAINS, ...

Exclude Domains: Enter all domains you want to exclude from searching in this text field, separated by returns. Use this to exclude domains blocking automatic bots like DEVONagent Pro, e.g., 'sciencemag.org' or 'slashdot.org', or to ignore sites you don't like (for example 'google.com'). Domains skipped because they match one or more entries in this list are marked as 'Skipped' in the *Log* tab of the *Search* window.

Exclude Links: Enter URLs you want to exclude from being searched.

> Note: Both fields also accept the '*' wildcards at the beginning or end of lines.

MENU EXTRA

The options in this tab determine if DEVONagent Pro's menu extra is automatically started when you log into your account, if the menu should show icon previews, how results are opened when selected, and what hotkey to use to call the menu.



GENERAL

- **Start at login:** The menu extra is started automatically when you log in.
- **Show icon preview:** Shows preview icons of the found pages in the menu.
- **Show text summary in menu:** Shows a short summary directly in the menu. Uncheck this option to keep the menu less crowded; you can always read the full summary in the tooltip.
- **Cancel search after opening a result:** Stops the search run as soon as you double-click a result to view it. This option has no effect when you open the result in the background.

SEARCH

- **Agent:** Downloads each result page and filter e.g. error pages.
- **Express:** Returns the results unfiltered.

In both cases DEVONagent Pro uses its unique artificial intelligence technology to rank the results, in *Express* mode only based on title, address, and a short summary, in *Agent* mode based on the full text of the page.

OPEN RESULTS

- **In DEVONagent Pro:** Results you select in the menu extra's menu are opened using DEVONagent Pro's browser.
- **In default web browser:** Results you select in the menu extra's menuThe results are opened using your default web browser.

HOTKEY

Click the button to record any key combination you like to call the menu extra. Using the hotkey will open the menu extra in OS X 10.7 Lion's fullscreen mode, too.

WEB

The options in this tab resemble the settings of most web browsers. They define how DEVONagent Pro's built-in web browser windows displays HTML documents and live webpages.



WEB CONTENT

These settings define how DEVONagent Pro treats special Web contents.

- **Enable plugins:** Check this option to use installed third-party plugins, e.g., Flash or RealPlayer.
- **Enable Java:** Check this option to run Java applets contained in or linked to webpages.
- **Enable JavaScript:** Check this option to run JavaScript scripts contained in webpages.
- **Block pop-up windows:** Check this option to block pop-up windows, which are often advertisements. Uncheck this option if the webpage you're visiting uses pop-up windows for actual content (which ome Web content management systems do).
- **Only automatic JavaScript windows:** Check this option to block only pop-up windows opened by JavaScript, instead of all pop-ups.
- **Block zooming:** Check this option to keep JavaScript from zooming the web browser window to full screen.
- **Block advertisment:** Check this option to block common inline advertisements provided by major search engines.
- **Zoom text only:** Check to scale only the text when zooming in and out of webpages. If unchecked, DEVONagent Pro uses Safari-4-style zooming.

IMAGES

Use these otions to define how DEVONagent Pro displays graphics in webpages.

- **Display images when the page opens:** Check this option to diplay webpages with images or uncheck to load them without

images. If unchecked, you may miss some information on graphic-oriented pages.
- **Animate images:** Check this option to run animated graphics; uncheck it to show the items statically.
- **Loop animations of images:** Check this to run animated graphics in a loop.

ACCEPT COOKIES

Cookies are little text files with information that webpages store on your computer to recognize you as a returning customer. While most cookies are harmless, you may want to control what is being stored on your hard disk.

- **Always:** Accepts all cookies.
- **Never:** Doesn't accept any cookies
- **Only from sites you navigate to:** Accepts cookies, but only from websites you navigate to, not from other sites, e.g., ad trackers.
- **Delete cookies on quit:** Deletes all stored cookies when you quit DEVONagent Pro.

> Note: *Delete cookies on quit* deletes the cookies for all WebKit-based web browsers including Safari. All these browsers use the same single cookie file.

STANDARD/FIXED-WIDTH FONT

Set the font you want to use for displaying webpages separately for variable-width and fixed-width text. Holding the ⌥Option key changes the *Select* buttons to *Reset* for resetting the font to the factory default.

(FEED) STYLE SHEET

You can further control the way DEVONagent Pro displays webpages by applying a CSS style sheed for changing the rendering on-the-fly.

- **Style Sheet:** Click *Select* and choose your own style sheet to apply it.
- **Feed Style Sheet:** DEVONagent Pro comes with a number of different style sheets for Atom/RSS/JSON news feeds. Choose your preferred style. You can use your own CSS styles for news feeds by placing them in '~/Library/Application Support/DEVONagent/StyleSheets' (restart DEVONagent Pro if necessary).

> Note: Applying an external CSS style sheet to webpages is an expert option. It heavily affects the rendering of all webpages in DEVONagent Pro, though it does not interfere with the search functionality of DEVONagent Pro.

TEXT ENCODING

Select your desired text encoding for displaying webpages. Generally the default setting, *Automatic* should work fine. If not, choose a more appropriate text encoding for your language.

WEBKIT DEVELOPER EXTRAS

Enable to use the standard WebKit developers extras in web browser, e.g., the element inspector or the JavaScript console.

TABS

Like many modern web browsers, DEVONagent Pro features tabbed browsing. This enables you to display multiple webpages in one web browser window and switch between them with tabs.



Use the following settings to activate tabbed browsing and define additional options. They resemble those available in Apple Safari.

- **Open links from applications:** Defines whether DEVONagent Pro shows pages requested by other applications, such as the Finder, in a new window or in a new tab in the current web browser window.
- **Enable Tabbed Browsing:** Switches tabbed browsing on or off. You can always create new tabs manually, but DEVONagent Pro will not open new tabs automatically or when you ⌘-click a link.
- **Select new tabs as they are created:** When checked, DEVONagent Pro automatically switches to a newly generated tab.
- **Always show tab bar:** When checked, the tab bar is always visible; when unchecked, DEVONagent Pro only shows the tab bar when at least two tabs are open.

> Note: The lower part of the preference window shows the keyboard commands for creating new tabs and opening links in new tabs, similar to Apple Safari. The keyboard commands may change with the options you select above.

BOOKMARKS

DEVONagent Pro makes the bookmarks defined in your favorite web browser available both in the *Go* menu and in a bookmark drawer in web browser windows.



BOOKMARKS

Select your favorite browser:

- Camino
- DEVONagent Pro
- Firefox
- Chrome
- OmniWeb
- Safari

DEVONagent Pro comes with its own bookmark management. Choose *DEVONagent Pro* in the list to use the integrated bookmark management. See also p. 62ff

BOOKMARKS BAR

Select whether DEVONagent Pro automatically mirrors Web servers announced via Bonjour, bookmarks stored

in DEVONthink Pro, and workspaces in the bookmarks pane in a web browser windows sidebar or the *Go* menu.

- **Include Bonjour:** List Web server announced via Bonjour.
- **Include DEVONthink:** List bookmarks from open DEVONthink databases. The bookmarks are retrieved when DEVONagent Pro starts up. Since they are cached, they remain available even when DEVONthink isn't open.
- **Include Workspaces:** List workspaces.

BOOKMARKS MENU

Select if you want to include Bonjour services in the *Go* menu.

- **Include Bonjour:** List Web servers announced via Bonjour in *Go* menu.

EMAIL

DEVONagent Pro can send you reports of schedules search runs by email. Tell DEVONagent Pro how it shall send you messages on this tab.



SEND EMAIL

Choose if you want DEVONagent Pro to send you email using Apple Mail or using the built-in email function. If you don't use Apple Mail, add your email account details:

- **Server Name:** Your SMTP server address
- **User:** Your SMTP user name
- **Password:** Your SMTP password
- **Port:** The port to use; usually the default port should work
- **SSL:** Check if you want to use a secure connection

EMAIL FONT

Set the font used for styled emails (rich text). Check *Send styled emails* to let DEVONagent Pro send summary emails as RTF text. Read more about sending summary email messages here.

UPDATE

Change the settings on this tab to choose when you want DEVONagent Pro to check for new versions: never, on startup, daily, weekly or monthly. DEVONagent Pro only checks for updates when the computer is connected to the Internet.



Click *Check Now* to immediately check for a new version.

> Note: This feature is not available when DEVONagent Pro was purchased through the Mac App Store.

MENU EXTRA

IN THIS CHAPTER

DEVONagent Pro adds a menu extra to the right-hand side of the menu bar that allows you to enter a query and search run at any time from the menu bar.



It looks similar to the Spotlight menu and works pretty much the same way:

- Choose a search set or plugin from the magnifying glass pop-up menu.
- Enter your query.
- Hit ↩ or *Enter*.

DEVONagent Pro runs the query and shows the results in the menu.

- A colored bar in the search field shows search progress.
- Point with the mouse at any result to show a tooltip with a preview and a text summary.
- Click the result to open it in DEVONagent Pro or your default browser. See also p. 78ff
- Hold the ⌥ or ⌘ modifier key to open results in the background.
- Drag results to the Desktop or other applications. Dragging to the Desktop creates bookmarks (.webloc); dragging to other applications inserts the web address.
- Navigate through the list with the *Up* and *Down* keys, press ↩ or *Enter* to open the result in your browser.
- Recall recent searches or recently used plugins or search sets from the magnifying glass pop-up menu.
- Click the ⊗ to clear your search.

SCRIPTS

IN THIS CHAPTER

Introduction	85
DEVONagent Pro's Scripts menu	86
Automator	88

DEVONagent Pro comes with a fully loaded AppleScript dictionary and several Automator actions that help you automate almost every aspect of your DEVONagent Pro workflow. Use the included scripts to perform regular tasks and as templates for creating your own scripts and Automator workflows.

INTRODUCTION

DEVONagent Pro features an AppleScript dictionary and Automator actions that automate the application and integrate it with almost every other application supporting AppleScript and Automator.

EXAMPLE SCRIPTS

To make it easier for you to start using and writing scripts, we deliver a slew of scripts with DEVONagent Pro that you can access in the *Scripts* menu (which shows a stylized *S* symbol as its title instead of the word Scripts). These scripts interact directly with selected items, the currently displayed webpage or a window. All scripts delivered with DEVONagent Pro are useable in your daily work and don't require modification.

INTEGRATING OTHER APPLICATIONS

In addition to the scripts that you use inside DEVONagent Pro, OS X features a global script menu that allows you to access certain scripts from any application on your Mac, e.g., your web browser or Apple Mail. When activated, the global script icon appears at the right side of the menu bar (like other menu extras such as the *AirPort signal strength* or the *Spotlight* icon). It appears with a black stylized *S* icon.

> Note: By using folders named after applications inside the '~/Library/Scripts/Applications' directory, it is also possible to make scripts application-specific. Such scripts will appear at the top level of the global script menu when the application they belong to is frontmost. This removes clutter and shows only scripts that make sense in the current application.

DEVONagent Pro does not come with scripts for other applications, but you can use the global script menu for creating application-specific scripts.

To activate the global script menu, do the following:

- Open the AppleScript Utility (located in '/Applications/AppleScript').
- Check *Show Script Menu in menu bar.*
- Uncheck *Show Library scripts* if you only want to see the scripts you have installed yourself.

To install your own scripts, copy them into the folder '~/Library/Scripts'. You can use subfolders to structure them in any way you like.

DEVONAGENT PRO'S DICTIONARY

DEVONagent Pro includes a large dictionary with commands, objects, and methods you can use for writing scripts that interact or extend DEVONagent Pro. To view the dictionary, open the Script Editor application (by default located in '/Applications/AppleScript'), select *File > Open Dictionary* and choose DEVONagent Pro in the window.

You can also add DEVONagent Pro to your Script Editor library. Select *Window > Library*, click the + button and choose DEVONagent Pro. This way you keep DEVONagent Pro's dictionary at hand.

LEARNING APPLESCRIPT

This documentation is not an AppleScript language guide. Please refer to Apple's AppleScript website, other online resources, or introductory and reference books for more information on the AppleScript language. Here are some links for you:

- The Ultimate Beginner's Guide to AppleScript
- MacScripter
- ScriptWeb
- Scripting Matters Trainings

- AppleScript for Absolute Starters (free PDF book)
- AppleScript: The Missing Manual
- AppleScript: The Definitive Guide

DEVONAGENT PRO'S SCRIPTS MENU

The internal scripts menu of DEVONagent Pro, located to the left of the *Help* menu, gives you access to pre-made scripts that extend DEVONagent Pro with additional, more specialized commands and functions. They are only visible from inside DEVONagent Pro.



Of course, you can easily modify all these scripts using AppleScript Editor, and the workflows using Automator. And you can add your own scripts and workflows--located in '~/Library/Application Support/DEVONagent Pro/Scripts'--to the menu. You can open this folder in the Finder using *Scripts > Open Scripts Folder*.

Keyboard shortcuts: If you want to add keyboard shortcuts to scripts in this menu, either use the System Preferences or add the shortcut description to the file name of the script in "~/Library/Application Support/DEVONagent Pro/Scripts" or "~/Library/Scripts". Example: "eMail Current URL (Mail)___Cmd-Alt-M.scpt". The naming convention is three underline characters followed by the shortcut description. "Cmd" stands for the ⌘Command, "Alt" for the ⌥Option, "Ctrl" for the ^Control, and "Shift" for the ⇧Shift keys.

Caching: All scripts in this menu are cached and therefore their properties are persistent until you quit and relaunch the application or DEVONagent Pro automatically updates the menu, e.g. after adding or removing scripts.

> Note: If you have modified the contents of the script menu and want to go back to the default set, delete the Scripts folder in "~/Library/Application Support/DEVONagent/". DEVONagent Pro will recreate this folder, including it's content, the next time you launch the application.

SCRIPTS INTERACTING WITH OTHER APPLICATIONS

- **Email Current Page (Mail):** Creates a new message in Apple Mail with the currently displayed webpage attached as webarchive. Webarchives contain the HTML code of the page including all embedded elements that are necessary to display them.
- **Email Current URL:** Asks for an email address and sends the URL of the currently displayed webpage by email to this address. This script does not use Apple Mail, but sends the message directly via the messaging framework of OS X. It requires that you have set up at least one email account correctly in Apple Mail.
- **Email Results (Mail):** Creates a new email in Apple Mail with the abstracts of all results in its body.
- **Post to del.icio.us:** Posts the selected items as bookmarks to del.icio.us.
- **Post to Twitter:** Posts the selected items to Twitter.

SCRIPTS WORKING WITH IMAGES

- **Download Embedded JPEG Images:** Downloads all JPEG images embedded into the currently displayed page to the default download location via the download manager.
- **Download Linked JPEG Images:** Downloads all JPEG images linked from the currently displayed page to the default download location via the download manager.
- **Open Linked JPEG Images in Tabs:** Opens all JPEG images linked from the currently displayed page in separate tabs, then closes the current tab.
- **Open Linked JPEG Images:** Opens all JPEG images linked form from the currently displayed page in separate web browser windows.

SCRIPTS WORKING WITH PAGES AND RESULTS

- **Download Objects of Results:** Downloads all found objects of the frontmost search window. The search needs to be run with an active scanner returning objects, e.g. *Embedded Images*.
- **Convert Results to RSS:** Creates an RSS feed file for the found or selected results and puts it into `~/Sites/rss`. Enable web sharing to easily view your feeds locally using your web browser by browsing to, e.g., `http://127.0.0.1/rss/mysearchset.rss`.
- **File Results in DEVONthink:** Files new results in DEVONthink. One group is created for each search set/query. This script can is used as a search set action.
- **Speak Titles of Results:** Speaks the titles of the found or selected pages.

SCRIPTS FOR THE TOOLBAR

By default this contains no scripts. Add your own scripts here and also add them to the toolbar of search and browser windows using *View > Customize Toolbar*.

SCRIPTS ARRANGING WINDOWS

- **Open last Safari session:** Opens the last Safari session in DEVONagent Pro.
- **Browsers Side-by-Side:** Arranges the currently open web browser windows side-by-side.
- **Tile Browsers:** Arranges the currently open web browser windows tiled to 800 pixel width.
- **Combine Windows:** Combines the currently open web browser windows as separate tabs in one window.
- **Windows to Full Screen:** Resizes all web browser windows to full screen.

AUTOMATOR

DEVONagent Pro also comes with a bundle of integrated Automator actions you can use to create your own Automator workflows.

To see which actions DEVONagent Pro provides, open Automator and select DEVONagent Pro in the applications list on the left hand side. If you do not see DEVONagent Pro in the *Library* list, use *View > Arrange Actions by > Application*. Select any action to show a short description about what the action does, and have a look at Automator's built-in help to learn more about how to create a workflow.

> Note: Cannot find the Automator action you need for your workflow? We're open to suggestions!

PLUGIN DEVELOPMENT

IN THIS CHAPTER

Creating Your Own Plugins 89
XML and JSON Keys 92

DEVONagent Pro comes with a long list of ready-to-use plugins for popular search engines. However, you easily can write your own plugins to query your favorite search engine. Here is all what you need. The tutorial gives you a jump-start on how to write your own plugins for DEVONagent Pro, e.g., for integrating a search engine we haven't thought of yet. And the XML and JSON keys descriptions explain all the XML tags/JSON keys you can use in developing the perfect plugin.

CREATING YOUR OWN PLUGINS

Do you have one or more favorite websites you would like to search using DEVONagent Pro? This document shows you how to create an XML plugin for DEVONagent Pro. It is a step-by-step tutorial that guides you through a real, practical example--one that is found in the list of plugins of the application.

It would be good to also have a look at the Keys sectionof this chapter. This describes the XML keywords in nitty-gritty detail.

DEVONagent Pro comes with an integrated plugin assistant that makes creating your own XML-based plugin convenient and easy. Let's create a simple plugin from scratch in six steps.

STEP 1

Open a web browser window for www.ipl.org in DEVONagent Pro or any other web browser. Then search for 'Test' and copy the 'Next >>' link leading to the second results page.

STEP 2

Choose *File > New Plugin*, paste the copied link, and replace 'Test' with '_agentQuery_'.



Enter a name and description (useful but not necessary). The *Search Engine* radio button is automatically selected by DEVONagent Pro.

The '_agentQuery_' placeholder is where DEVONagent Pro inserts the search term when using the plugin. The '_agentOffset_' placeholder, which is used by DEVONagent Pro to jump from result page to result page,

is automatically inserted instead of the '10' of the '&next=' parameter after clicking the *Add* button.

STEP 3

Let's test the plugin. In this case, the created plugin is fully functional but is causing unnecessary traffic and might return unexpected results. Therefore, select any 'www.ipl.org' URL in the log and choose *Exlude Domain* in the contextual menu. This excludes all pages on ipl.org from becoming possible results.



STEP 4

Retry the test. In the log you can see that DEVONagent Pro uses now 27 links per page returned by IPL. But not all of them are actual results, therefore we could exclude additional, static URLs like:

- ischool.syr.edu
- ischool.uw.edu
- theipl.wordpress.com
- theipl2blog.wordpress.com
- twitter.com/theipl
- www.delicious.com/TheInternetPublicLibrary
- www.diigo.com/user/Theipl2
- www.facebook.com/pages/Internet-Public-Library
- www.ipl.org
- www.ischool.drexel.edu
- www.ischool.pitt.edu
- www.ischool.utexas.edu
- www.myspace.com/internetpubliclibrary
- www.youtube.com/iplcommunity

Or we could have a closer look at the results page and its HTML source. Just double-click on the results page in the log to open a browser window, then switch to the HTML source. All unncessary links are part of the footer, right after "Connect With Us On". Therefore it's sufficient to add this snippet to the plugin's code:

```
<key>LinksEnd</key> <string>Connect With Us On</string>
```

Retry the test once again. Finally DEVONagent Pro uses 10 links per page as expected.



STEP 5

Finally, uncheck all operators since IPL does not support them.



That's it!

In other cases, you might also want to look at the source of the plugin and validate the values for 'Start', 'OffsetPerPage', and 'ResultsPerPage', or add 'LinksMatching' definitions etc. Site-specific search engines may also require 'TitleStart'/'TitleEnd', 'TextStart'/'TextEnd', 'DateStart'/'DateEnd', 'NoTopics', or 'CrawlDelay' definitions. See also p. 92ff

In addition, DEVONagent Pro may not always be able to insert the '_agentOffset_' and '_agentNumber_' placeholders automatically. You might have to do this on your own; otherwise, only the first results page is used.

FINETUNING

We now have a working plugin for IPL. While we might have received links, we didn't necessarily get good data. You can check both the pages and digest panes in the search window to fine tune your plugin. If DEVONagent Pro extracts too much data from the result list pages, you can use the following keys to tell the software what constitutes a result link and what doesn't.

- **1. TitleStart and TitleEnd:** Extract the title of the article.
- **2. TextStart and TextEnd:** Extract the article text.
- **3. DateStart and DateEnd:** Extract the article's date.
- **4. NoTopics:** Suppress common topics that always occur for any search on a site.
- **5. PostScan:** Scan the results for the string you where searching for.

To determine values for these parameters, you will need to look at the source code of a couple of articles, and try to find strings that can be used for these keys. When looking at the topics in the digest pane after you've done your searches, you can set the 'NoTopics' list. Any word that should not be included as a topic can be added to this list.

CONGRATULATIONS

With the steps described in this tutorial, you should be able to go through the steps of writing a plugin yourself. With a bit of practice, it is possible to write an optimized plugin that will deliver good results for DEVONagent Pro to work with. It might help to look at the additional plugins that already come with DEVONagent Pro before designing your own plugin.

And remember: If you think your plugin is great for others, please share it with us!

XML AND JSON KEYS

XML-based plugins use Apple's ".plist" file format; therefore, it's possible to edit them using Property List Editor or any text editor like TextEdit, SubEthaEdit or Xcode/ProjectBuilder. JSON-based plugins are simple text files that you can also edit using any plain text editor.

DEVONagent Pro loads all plugins inside its application package or stored in the folder "~/Library/Application Support/DEVONagent Pro/Plugins". If DEVONagent Pro is not able to load a plugin, the file is logged to the console. You can also place aliases or symbolic links to plugins here.

LOCALIZATION

The following XML and JSON plugin keys can be suffixed with a language identifier to use language-specific search engines: *EngineUrl*, *EngineNextUrl*, *KeywordsUrl*, and *NextLinkName*. Language identifiers are: DE, DA, NL, ES, HU, FR, IT, CS, PT, PL, SV, FI, EN, NO, RU, EL, AR, and HE.

> **Example:** A URL in the key *EngineUrl_DE* is used to target the German variant of a search engine.

NECESSARY KEYS

- **Name:** [string or dict] The name of the plugin. Example: "BBC News".
- **Info:** [string or dict] Information containing name, version and copyright. Example: "BBC News Plugin 1.0 © 2003--2005 DEVONtechnologies".
- **Description:** [string or dict] Describes the functionality of the plugin. Example: "Queries the BBC news archive."
- **Version:** [string] The version number (format major.minor). Example: "1.0".
- **Identifier:** [string] Unique identifier (format domain.name.plugin). Example: "com.devon-technologies.bbcnews.plugin".
- **EngineUrl:** [string or array of strings] The Internet address(es) of the search engine. The strings "_agentQuery_", "_agentNumber_" and "_agentOffset_" are replaced by the search term, the number of results and the offset of the current page. "_agentNumber_" and "_agentOffset_" are optional. '_agentLanguage_' is replaced by the language used by the plugin (ISO 639 two-letter codes). Can contain the placeholders "_agentUser_" and "_agent_Password_" for HTTP authentification. Example: "http://www.bbc.co.uk/cgi-bin/search/results.pl?tab=news&start=_agentOffset_& go=homepage&q=_agentQuery_".

> Note: Name, Info and Description can be localized. Specify a dictionary containing key/string pairs for multiple languages. The key contains the name of the language, e.g., German or English.

ADDITIONAL KEYS

- **CrawlDelay:** [float] Minimal delay between two requests sent to the same server.
- **DateEnd:** [string or array of strings] String marking the end of the range of the HTML source code containing the date of a page.
- **DateStart:** [string or array of strings] String marking the beginning of the range of the HTML source code containing the date of a page. Note that "DateEnd" is optional if "DateStart" is specified. Useful if server provides no dates or the wrong dates (for example a Usenet query using Google).
- **EncodingPage:** [string] Default character encoding for result pages (default: Latin-1). Examples: "ISO-8859-1", "UTF-8", "ISO-8859-2", "Shift-JIS".
- **EncodingUrl:** [string] Character encoding for search term "_agentQuery_" (default: Latin-1). Examples: "ISO-8859-1", "UTF-8", "ISO-8859-2", "Shift-JIS".
- **EngineNextUrl:** [string or array of strings] The Internet address(es) of the search engine(s) used for subsequent pages (if not identical to the address of the first page). The strings "_agentQuery_", "_agentNumber_" and "_agentOffset_" are replaced by the search term, the number of results and the offset of the current page. "_agentNumber_" is optional.
- **EngineRelated:** [string] Defines a URL for a 'see also' function of the search engine.
- **EngineSite:** [string or array of strings] Defines (a) (sub)domain(s) with or without a path to search. DEVONagent Pro uses an appropriate common search engine to perform the search. Example: 'devontechnologies.com/products/'.
- **ExcludeLinksNamed:** [array of strings] Defines an array of names of links which should be skipped.
- **FileTypes:** [string] List of all supported file types: html, feed/rss, text, pdf, OpenOffice, Microsoft/Word, RTF or all. Default is 'all'.
- **FilterLanguage:** [Boolean] Enable or disable filtering by language.
- **FilterSimilarPages:** [Boolean] Enable or disable DEVONagent Pro's Similar Pages filter (default: true).
- **FollowLinks:** [Boolean] Enable or disable DEVONagent Pro's Follow Links option (default: true).
- **GoogleTags:** [Boolean] Defines whether 'googleon'/'googleoff' tags should be supported.
- **HTTPShouldHandleCookies:** [Boolean] Defines whether cookies should be handled by HTTP or not.
- **Keyword:** [string or array] One or more unique keywords used for quick searching (like "Mozilla Keywords") by entering the keyword followed by the search term in the URL field of the browser window.
- **KeywordsUrl:** [string] Defines an alternate URL used for the Mozilla-like keywords in the browser's address bar.
- **LinksEnd:** [string or array of strings] String marking the end of the range of the HTML source code containing the links to use (any position after the last link to use but before the next link). Example: "-- Footer Area --".

- **LinksMatching:** [string or array] Only links of result pages matching this string or these strings are used (prefix/suffix * wildcards are supported). Examples: "*news.bbc.co.uk/*".
- **LinksNotMatching:** [string or array] Only links of result pages not matching this string or these strings are used (prefix/suffix "*" wildcards are are supported).
- **LinksStart:** [string or array of strings] String marking the beginning of the range of the HTML source code containing the links to use (any position before the first link to use and after the last link to ignore). Note that "LinksEnd" is optional if "LinksStart" is specified. Example: "search results for".
- **LoginPost:** [string] Defines the optional HTTP POST parameters. Usage like "Post". Can contain the placeholders "_agentUser_" and "_agent_Password_".
- **LoginURL:** [string] The address used to log into a website. Usage similar to "EngineUrl". Can contain the placeholders "_agentUser_" and "_agent_Password_".
- **NextLinkStart:** [string] Defines the start of the range for the 'next results page' link.
- **NextLinkEnd:** [string] Defines the end of the range for the 'next results page' link.
- **NextLinkName:** [string] Defines the name of the link for the 'next results page' (instead of having to use NextLinkStart/End).
- **NoTopics:** [array or string] Array of strings or string containing separated words to ignore in the topics list. Add site specific words here.
- **OffsetPerPage:** [integer] Increase for "_agentOffset_" after every page (default: 1).
- **Operators:** [integer] Bitmap describing the possibilities of the search engine and the required syntax (see below). The default value is 59 (1+2+8+16+32), meaning that AND, OR, NOT, phrases and parenthesis are supported.
- **OperatorsDictionary:** [dict] A dictionary containing key-string pairs to convert the name of operators to a different name required by the search engine. Possible keys are "AND", "ANDNOT", "OR", "NOT", "XOR", "NEAR", "BEFORE", "AFTER", "-".
- **ParseLinks:** [Boolean] Parse and unify links of common search engines (Google, Yahoo, Alltheweb, Altavista & Ask Jeeves) (default: false).
- **Post:** [dict or string] Send a HTTP POST instead of a HTTP GET action using this form data. Note: The strings of the form data can contain "_agentQuery_" and "_agentNumber_" placeholders.
- **PostScan:** [Boolean] Tell DEVONagent Pro to check if the retrieved pages match the search term (true), or to accept all (false) pages (default: true).
- **ResultsPerPage:** [integer] Number of results per page and maximal value for "_agentNumber_" (default: 10).
- **RequiresCrawling:** [Boolean] Marks this plugin as needing crawling.
- **RequiresThumbnails:** [Boolean] Marks this plugin as using only thumbnailed links. Crawling needs to be skipped.
- **RoundResultsPerPage:** [integer] Always round number of results per page ("_agentNumber_") to multiples of this value (default: 10).

- **ScanTerm:** [string] String specifiying a term used to filter results (e.g. instead of or in addition to the secondary query defined by the user).
- **SkipsCrawling:** [Boolean] Marks this plugin as skipping crawling.
- **Start:** [integer] The initial value for "_agentOffset_" (default: 0).
- **StripTags:** [array] Array of strings marking HTML tags defining blocks to strip.
- **TextEnd:** [string or array of strings] String marking the end of the range of the HTML source code containing the relevant text of a page. "TextStart" is optional if "TextEnd" is specified.
- **TextStart:** [string or array of strings] String marking the beginning of the range of the HTML source code containing the relevant text of a page. Note that "TextEnd" is optional if "TextStart" is specified. Useful if you're querying a specific site (all results have the same layout) to skip headers, footers or navigation of a page. This improves plain text display, digest and summarization.
- **TextTags:** [array] Array of strings marking HTML tags defining blocks to convert to text.
- **Timeout:** [integer] Sets the timeout for requests; default is 60 seconds.
- **TitleEnd:** [string or array of strings] String marking the end of the range of the HTML source code containing the title of a page.
- **TitleStart:** [string or array of strings] String marking the beginning of the range of the HTML source code containing the title of a page. Note that "TitleEnd" is optional if "TitleStart" is specified. Only useful if all results have identical or no titles (for example a Usenet query).
- **UseListingResults:** [Boolean] Treat the returned pages as results (and not as pages linking to the results). All "Links..." keys are unused in that case.
- **UserAgent:** [string] Custom HTTP user agent string.

JSON AND XML-SPECIFIC KEYS

- **ResultsKeyPath:** [string] The JSON key path to the results in the JSON output.
- **DatesKeyPath:** [string] The JSON key path to the result dates relative to ResultsKeyPath.
- **LinksKeyPath:** [string] The JSON key path to the links relative to ResultsKeyPath.
- **TitlesKeyPath:** [string] The JSON key path to the titles relative to ResultsKeyPath.
- **DescriptionsKeyPath:** [string] The JSON key path to the descriptions relative to ResultsKeyPath.
- **ContentsKeyPath:** [string] The JSON key path to the contents relative to ResultsKeyPath.
- **ThumbnailsKeyPath:** [string] The JSON key path to the thumbnails relative to ResultsKeyPath.

NOTES

Operator Bitmap: The following table gives you the necessary values for calculating the operator bitmap for the "Operators" key (see above):

- **0 [value: 1]:** Supports AND operator
- **1 [value: 2]:** Supports OR operator

- **2 [value: 4]:** Supports XOR operator
- **3 [value: 8]:** Supports NOT operator
- **4 [value: 16]:** Supports "" phrases
- **5 [value: 32]:** Supports () parenthesis
- **6 [value: 64]:** Supports NEAR operator
- **7 [value: 128]:** Supports AFTER operator
- **8 [value: 256]:** Supports BEFORE operator
- **9 [value: 512]:** Supports NEXT operator
- **11 [value: 2048]:** Use ANDNOT instead of NOT or '-'
- **12 [value: 4096]:** Convert search term to lower case
- **13 [value: 8192]:** Convert search term to upper case
- **14 [value: 16384]:** Engine scans for any word by default (not for all words) without an explicit operator
- **15 [value: 32768]:** Use AND/NOT instead of '+'/'-'
- **16 [value: 65536]:** Use # instead of OR
- **17 [value: 131072]:** Supports OPT operator

LinksStart, et al.: 'LinksStart', 'LinksEnd', 'LinksMatching', and 'LinksNotMatching' are three different ways to specify interesting links of a page. Specify none, some, or all of them depending on the search engine you are accessing. The more you specifiy, the higher the chances are that the plugin will still work after the structure of the HTML code or the links changed.
First DEVONagent Pro retrieves links using 'LinksStart'/'LinksEnd', then it filters them using 'LinksNotMatching', and finally it matches them against 'LinksMatching'.

Links vs. Results: 'LinksStart'/'LinksEnd, 'LinksMatching', and 'LinksNotMatching' are used for pages listing the results, 'TextStart'/'TextEnd', 'TitleStart'/'TitleEnd', and 'DateStart'/'DateEnd' are used for the result pages.

FollowLinks: 'FollowLinks' applies to result pages only; the links of pages listing results are always used!

No case: All string values are case insensitive.

TROUBLESHOOTING

IN THIS CHAPTER

DEVONagent Pro behaves irrationally 97
Problems interacting with DEVONthink 97

DEVONagent Pro was created with robustness in mind. But any computer hardware and software can write defective data or destroy files. If you have trouble with this application, please refer to the methods below, and also have a look at our FAQ.

DEVONAGENT PRO BEHAVES IRRATIONALLY

No software on this planet is bug-free. If an application behaves irrationally, there is a good chance that your have just found a bug. But there may be another: The application package could have become damaged, e.g, during an update or through a bug in an unrelated piece of software on your computer.

If DEVONagent Pro crashes or you have found a bug, please send us a bug report.

STRANGE APPLICATION BEHAVIOR

If something happens like the following

- menus disappearing or silently refusing to do anything,
- windows showing graphical artifacts,
- or applications not opening or opening with strange error messages,

please try to trash the application package. Then empty your web brower's cache, re-download the software in question, and re-install it. In many cases this cures the problem.

If this does not help, try deleting DEVONagent Pro's preferences files located in '~/Library/Preferences' and starting with 'com.devon-technologies.agent'. Access your LIbrary folder by visiting the *Go* menu in the Finder with the ⌥ key held down.

STRANGE BEHAVIOR OF TABS

With Zooom/2 installed, tabs in tabbed windows behave stragely, e.g., close by just hovering the cursor over the tab. Another effect of Zooom/2 are scrolling problems. Disabling Zooom/2 solves the problem.

PROBLEMS INTERACTING WITH DEVONTHINK

DEVONagent Pro uses OS X's Services internally to transfer data to DEVONthink. If DEVONagent Pro beeps when you try to transfer data to DEVONthink, the most likely reason for this problem is that there's something wrong with the Services.

You can use the third party application Service Scrubber to try and modify this behavior; Service Scrubber should allow you to enable/disable services, rename them, or give them new keyboard shortcuts. Some of these modifications, however,

can lead to communication problems between DEVONthink and DEVONagent Pro. Restore to the default settings to enable the DEVONagent Pro/DEVONthink link again.

TECHNOLOGY

IN THIS CHAPTER

General Concept 99
Features 99
Structure 99
Applications 100

All commercial DEVONtechnologies applications are based on a proprietary AI technology, with rock-solid database foundation that allow them to manage large numbers of documents or knowledge bits while analyzing them almost instantly at the same time.

GENERAL CONCEPT

DEVONtechnology, on which all DEVONtechnologies' applications are built, is a new technology at the very beginning of its development. DEVONtechnologies constantly improves the technology and enhances it for more functionality, efficiency, robustness and flexibility.

Development of the DEVONtechnology is a battle on two main forefronts of information processing technology. DEVONtechnologies is working hard on unifying both the top-down and the bottom-up AI concepts by imitating high-level functions and simulating the basic functionality of natural systems. This leads to highly functional, fast and efficient AI systems that can be used in a great variety of information processing contexts, such as pattern recognition, signal processing and information storage and retrieval.

FEATURES

The DEVONtechnology is a rock-solid foundation suitable for a variety of completely independent applications. Therefore it is ideal for the rapid development of a huge range of new database-, signal-processing- and language-analysis-driven applications. The ability to deal with any kind of digital data makes it extremely flexible.

The size of DEVONtechnology-based databases can, depending on the type of data stored, grow logarithmically and make indexing is completely unnecessary. Also, applications based on the DEVONtechnology improve themselves continuously (the more data they handle, the better the results), are language-independent and iron out any irregularities by applying fuzzy logic.

STRUCTURE

The DEVONtechnology consists of a kernel and several layers. Together they perform all the underlying computing, from 'simple' data handling to complex signal processing.

Kernel: The kernel is the foundation for all layers and applications and is responsible for data handling, semantic and associative data processing, signal processing, fast statistic analyses and all fuzzy algorithms. It has to be as fast, flexible, and extensible as possible; it is 64-bit aware and uses a generic, proprietary file format (see above)

allowing it to verify and repair low level data consistency, featuring logarithmic growth of the database and logarithmic speed decrease with increasing database size. The DEVONtechnology kernel is Unicode-aware, completely language-independent and self-optimizing and self-organizing.

Layers: The layers form a shell around the kernel and provide high-level functions for the applications built on top of them. The database layer, for example, is used to store and organize data and supports all kinds of relations (1:n, n:1, n:n), hierarchies and freeform databases. No indexing or primary keys are required, strings can be unlimited in size and it's possible at any time to extend the range of pre-defined data types (Boolean, character, float, double, signed, unsigned, string, date, time, blob, color, size, and point). Another layer, the XML layer, makes it easy to handle XML code within the DEVONtechnology; it has a very small overhead, compared to DOM parsers or available XML databases, requires no indexing and supports the tight integration of other databases (and vice versa).

APPLICATIONS

Some of the most likely applications for the DEVONtechnology are databases (knowledge bases, expert systems, search engines, table-of-content-generators, instant data-mining), intelligent agents, encryption, compression and archiving. Other uses for DEVONtechnology may be chat-bots, context-sensitive help, optical character recognition (OCR), speech analysis, recognition and synthesis, staticstics, thesauri and automatic translations.

In particular, applications dependant on processing human language, either written or spoken, benefit from the flexible technology foundation. So, DEVONtechnologies' main focus in the development of new applications is in these areas: databases, 'intelligent' agents, text and speech analysis, statistics.

Look forward to see a great range of different applications based on the DEVONtechnology. A few have already been announced on the DEVONtechnologies web site: www.devontechnologies.com.

OTHER PRODUCTS

IN THIS CHAPTER

Overview	101
DEVONthink	101
DEVONagent	101
DEVONsphere	102
Needful Things	102

Besides DEVONagent Pro, DEVONtechnologies publishes a number of other commercial, shareware, and freeware applications and services that might be helpful for you.

OVERVIEW

DEVONtechnologies is focused on developing innovative applications for finding, storing, and organizing information. Our main objective is to make complex yet flexible technology that is both easy to use and lightning fast. All applications are based on the DEVONtechnology, a powerful and solid core unique to DEVONtechnologies.

- DEVONthink
- DEVONagent
- DEVONsphere

We also publish some freeware apps and services for your everyday work with your Mac.

NEWSLETTER & COMMUNITY

Would you like us to keep you informed about updates and new product releases? Visit our blog and subscribe to our free newsletter.

If you have a moment feel free to visit our lively user community. Here users of all skill levels meet to discuss our applications, talk about our technology, and exchange tips and tricks for DEVONagent Pro & Co.

DEVONTHINK

Organize and work with all your documents, bookmarks, email messages, text files, images, PDFs, in one place, regardless where they originated. Quickly capture data without interrupting your workflow. DEVONthink's unique AI assists you in getting the most out of your data collection.

- Learn more about DEVONthink
- Check your upgrade options if you want to upgrade to a higher edition

DEVONAGENT

DEVONagent Pro helps you search more efficiently on the web. It searches multiple sources, frees you from hunting for the really relevant results, and gives you power tools for your research. DEVONagent Express and DEVONagent Lite (free) make searching the web as easy as using Spotlight. Search Google, Bing, YouTube, Facebook, Twitter, even the Mac App Store, right from the menu bar.

Learn more about DEVONagent Pro.

DEVONSPHERE

Make your Mac smarter: Let DEVONsphere Express keep track of related emails, articles on the same subject, and similar web pages. Discover the hidden connection between seemingly unrelated files.

Learn more about DEVONsphere Express.

NEEDFUL THINGS

Search files on your hard disk, watch web cams, create thumbnails, or access all your files and apps from the menu bar. Reformat paragraphs in your favorite word processor or do little calculations anywhere you can type in text. All for free.

Learn more about our freeware apps and services.

APPENDIX

IN THIS CHAPTER

Glossary	103
FAQ (product-specific)	104
List of Search Sets	105
List of Plugins	106
List of Scanners	112
Log message codes	113

GLOSSARY

Become familiar with these terms to get the most out of working with DEVONagent Pro.

KEYBOARD SYMBOLS

- ⌘ The *Command* key, usually next to the *Space* bar.
- ⌥ The *Option* key.
- ^ The *Control* key (usually labeled with "ctrl").
- ⇧ The *Shift* key.
- ⇥ The *Tab* key.
- ↩ The *Return* key.

INTERFACE ELEMENTS

- **Alternative menu item:** Some menu items have less frequently used counterparts that are hidden by default. Press the ⌥Option key when visiting the menu or contextual menu to make them appear.
- **Contextual Menu:** The menu that appears when you right-click, or click on something with the ^ *Control* key held, something; the contextual menu gives you access to frequently used commands that deal directly with the clicked object. See also p. 51ff
- **Plugin:** Modules that act as the connector between DEVONagent Pro and search engines. Each plugin is the interface for one or more search engines. In addition, plugins can extend DEVONagent Pro with other functionality, e.g., scanners. DEVONagent Pro knows two types of search engine plugins: Cocoa-based (compiled) plugins, and XML-based plugins that can be created using the *Plugin Assistant* or using a simple text editor. See also p. 106ff
- **Scanners:** Plugins that act as filters for formal criteria such as 'is a thumbnail gallery' or 'contains links to Word documents'. Scanners are used to refine a search. See also p. 112ff
- **Search Window:** A window in DEVONagent Pro that lets you select a search set, type in a query, start the search run, and view the search results. See also p. 52ff
- **Topics:** A list of words extracted by DEVONagent Pro from search results--generally the most important words in the found documents. Topics can be selected in the search window to focus the visualizer to this topic. See also p. 53ff
- **Visualizer:** A graphic representation of topics and their relationships. The graphic looks like a 'spider web,' with 'bubbles' representing each topic. See also p. 53ff

OPERATORS, QUERIES, SEARCH SETS

- **Boolean operators:** Boolean operators are AND, OR, and NOT. They are used to define how words or parts of search terms relate to each other. Example: 'steve AND jobs'. See also p. 25ff
- **Query:** A 'question' sent to one or multiple search engines through a search engine plugin. The query (the question) is written in a formalized style using search words, Boolean operators, and parentheses. See also p. 25ff
- **Search engine:** A computer that keeps an index of documents or information and that can be searched by providing it with a query. Search engines are generally used through a web browser. DEVONagent Pro emulates this human-computer interaction through plugins.
- **Search results:** A pool of documents or links to documents, e.g., webpages or PDF documents, returned by a search run.
- **Search run:** The process of sending a query to one or multiple search engines.
- **Search set:** A set of parameters that defines how DEVONagent Pro conducts a search run. Search sets contain which search engine plugins shall be used, which scanners shall be applied, and what to do with the search results when the search run is completed. See also p. 29ff
- **Search term:** See above: Query. See also p. 25ff

FAQ (PRODUCT-SPECIFIC)

Is DEVONagent Pro an add-on to DEVONthink? Although we sell DEVONagent Pro with DEVONthink in a bundle, it is a stand-alone application. Many of our customers use DEVONagent Pro for their research work, but don't necessarily archive the results in DEVONthink.

Can I write my own plug-ins for DEVONagent Pro? Sure. The complete documentation on how to make plug-ins for DEVONagent Pro is included in DEVONagent Pro's online documentation.

Can I search my hard disk instead of the Internet? Not with the current version of DEVONagent Pro, no. However, our freeware application EasyFind is able to preview found documents and highlight occurrences in file names. And, of course, there is still Spotlight.

How can I search already archived pages Open the archive (Tools & Open Archive) and use the search field there.

What advantages does DEVONagent Pro have over Google & Co? The most important advantages over web search engines like Google are:

- DEVONagent Pro comes with an innovative visualizer.
- DEVONagent Pro can query multiple search engines simultaneously.
- Scanners look for certain kinds of webpages, e.g., pages with webcams, thumbnail galleries, videos, etc.
- DEVONagent Pro removes duplicate URLs/ webpages, advertisements, spam, and HTTP errors.
- DEVONagent Pro also removes similar pages on demand.
- DEVONagent Pro scans the current contents of the pages; therefore, it doesn't return wrong results from outdated search engine indexes

- DEVONagent Pro supports more advanced operators like NEAR, BEFORE, and AFTER
- DEVONagent Pro can follow promising links automatically.
- DEVONagent Pro provides more useful and complete summaries in the Pages tab and complete digests based on selected/entered topics or the used query.
- You can easily find similar results ("See Also"), archive results or transfer them to DEVONthink.

Why does DEVONagent Pro crash when displaying PDFs? DEVONagent Pro can crash when trying to display PDF files on Macs with Adobe Acrobat installed. Acrobat's browser plugin is incompatible to the web browser engine of both OS X and DEVONagent Pro. Remove the Acrobat plugin from "/Library/Internet Plug-Ins" and everything should work as advertised.

Why does DEVONagent Pro crash when I open a browser window or an archived page? DEVONagent Pro uses Apple's WebKit as its browser engine. When WebKit crashes it draws DEVONagent Pro with it into the abyss and there is little we can do about it. So most DEVONagent Pro crashes related to browsing are, in fact, WebKit crashes. Please send us your crash log (in ~/Library/Logs/CrashReporter/) if you want to know what happened.

How do I completely uninstall DEVONagent Pro? To completely remove DEVONagent Pro from your Mac, see the instructions in the Read Me.

LIST OF SEARCH SETS

Search sets are sets of parameters and options that control which search engines are used for a search run, which sites are crawled directly, what is filtered, and what is done with the returned results. DEVONagent Pro comes with a number of example search sets to get you started:

- **Apple (Feeds):** Crawls some RSS feeds (Downloads, PR and Hot News) provided by Apple.
- **Marketing:** Crawls more than 200 IT and Macintosh related news sites and feeds (the default query looks for news related to DEVONtechnologies).
- **Mac > Latest Software:** Crawls some software trackers and directories for new releases.
- **Mac > Latest News:** Crawls the most popular Macintosh news sites and feeds.
- **Web (Scanner) > Movies:** Queries the Web plugin and scans the results for linked movies and videos.
- **Web (Scanner) > Thumbnail Galleries:** Queries the Web plugin and scans the results for thumbnail galleries.
- **Web (Scanner) > Downloads:** Queries the Web plugin and scans the results for downloadable archives.
- **Web > Deep:** Queries Bing, Exalead, Google and Yahoo plugins (up to 100 results per plugin).
- **Web > Deeper:** Queries Bing, Exalead, Google and Yahoo plugins (up to 100 results per plugin) and follows links (one level).

- **Web > Deepest:** Queries Bing, Exalead, Google and Yahoo plugins (up to 100 results per plugin) and follows links (maximum level).
- **Web > Fast:** Queries the Web plugin (up to 100 results), but does not follow links to return results as soon as possible.
- **Web > Express:** Queries the Web plugin (up to 60 results) in express mode (no filtering).

Start with the *Web > Fast* search set for your first search runs, then use the *Search Sets* window to make your own or adapt an existing one for your requirements. See also p. 29ff

To build your own search set consider buying DEVONagent.

LIST OF PLUGINS

Technically, plugins are collections of URLs and procedures that DEVONagent Pro uses to access search engines on the Web. They are either written in Cocoa or in human-readable XML (plain text with special syntax). In addition to simple HTML queries, DEVONagent Pro also supports and analyzes Atom, RSS, and JSON feeds.

In the list below, you will find the associated quick search keywords in brackets. You use quick search keywords to send a query to a plugin directly from the address bar of a *web browser window*. *You can change the quick search keyword in the Plugins & Scanners* panel.

> Note: Some sites need a valid log-in. If you want to query these sites with a plugin, you need to enable cookies and manually log in with your web browser in advance. When you use DEVONagent Pro, the websites then will recognize you as a returning user. You will find a note in the plugin description if a site requires a log-in.

SEARCH

> Note: DEVONagent Pro presents this category separately in its menu, above the other plugins to make them more easily accessible.

- **Baidu:** Searches the web using Baidu.
- **DuckDuckGo:** Searches the web using DuckDuckGo, a search engine that claims that it doesn't track its users and delivers unbiased results (see also: filter bubble).
- **Google:** Searches the web using Google. Google is famous for ranking websites by the number of other sites linking to it. Google is now widely recognized as the world's largest search engine.
- **Google (PDF):** Searches for PDFs using Google.
- **Qwant:** Searches the web using Qwant, a search engine that, like DuckDuckGo, claims that it doesn't track its users and has no filter bubble.
- **StartPage:** Searches the web using StartPage. The search engines uses results from Google and claims that it respects its users' privacy and has no filter bubble.

- **Web:** Searches the web using Bing, Google, and Yahoo. Depending on the system language, DEVONagent Pro also uses local search engines or local variants.
- **Yahoo:** Searches the web using Yahoo, one of the three major search engines.
- **Yandex:** Searches the web using Yandex.

APPLE

- **App Store:** Searches Apple's App Store.
- **Developer Connection:** Searches the Apple Developer Connection database, the number one source for OS X developers.
- **Knowledge Base:** Searches the Apple Knowledge Base, the #1 resource for finding technical information about Mac computers, Mac OS and Apple software.
- **Macintosh News:** Scans major Macintosh news sites, namely Macworld, MacCentral, Macintouch, and MacNN.Use this plugin to stay up-to-date about everything Macintosh.
- **MacUpdate:** Searches for OS X software using Macupdate. MacUpdate watches for the latest Macintosh software updates and visits over more than 800 websites a day, looking for version changes to software titles not submitted by developers.

BLOGS

- **Google Blog Search:** Searches blogs using Google Blog Search.

BROWSERS

- **All Cached Pages:** Scans all pages cached by earlier search runs. Use this to include already scanned pages again in a new search.
- **Bookmarks:** Scans all websites bookmarked in DEVONagent, Safari, OmniWeb, Camino, Chrome, or Firefoxfor the search query. You can use this plugin to create your private mini-web with bookmarks and search only this collection.
- **DEVONthink databases:** Searches all web sites bookmarkes in the currently opened DEVONthink databases.
- **DEVONthink server:** Searches shared DEVONthink Pro Office databases through the local web server. DEVONthink Pro Office has to be running and web sharing started by the same user.
- **History:** Scans the pages you have visited recently with Safari or DEVONagent Pro for the search query. This is useful for searching for something you remember you have seen recently, but you cannot remember where.

COMPUTER SCIENCE

- **ACM Digital Library:** Searches the digital library of the Association for Computing Machinery.
- **Apple Cocoa-Dev:** Searches Apple's cocoa-dev mailing list. This is very useful if you do OS X software development.

- **Citeseer:** Searches the CiteSeer library. Citeseer is a scientific literature digital library and search engine that focuses primarily on the literature in computer and information science.
- **Cocoabuilder:** Searches Apple & Omnigroup Cocoa mailing lists using Cocoabuilder. Very useful if you do OS X software development.
- **GitHub Code Search:** Searches GitHub for code.
- **Ohloh Code Search:** Searches for open source code examples and projects using Ohloh. ohloh.net is a free search engine for open source code.
- **Stack Overflow:** Searches Stack Overflow for answers to development questions.

DICTIONARIES

- **Acronym Finder:** Searches Acronym Finder, the world's largest and most accurate dictionary of acronyms, abbreviations and initialisms.
- **Dictionaries:** Looks for word definitions in online dictionaries, namely Reference.com and Hyperdictionary.
- **Infoplease:** Searches Infoplease, a reference source that combines the contents of an encyclopedia, a dictionary, an atlas, and several almanacs with statistics, facts and historical records.
- **Onelook:** Searches for word definitions or translations using Onelook. Onelook is a search engine that provides access to web-based dictionaries that define or translate words.
- **Wiktionary:** Looks for word definitions in the online dictionary Wiktionary. Wiktionary is a free multilingual dictionary and thesaurus that's being written collaboratively. Anybody can edit any article and a record of changes is kept. This plugin is localized and searches in the selected language.

DIRECTORIES

- **Open Directory:** Searches the Open Directory. The Open Directory (Dmoz.org) seeks to be the largest free web catalog.
- **WoW:** Searches the WoW catalog. WoW categorizes websites by country, state or region and uses a professional editorial team.
- **Yahoo Directory:** Searches the Yahoo directory. The Yahoo directory was the world's first professionally edited web directory. It is currently divided into 14 main categories.

DISCUSSION LISTS

- **DEVONtech Forum:** Searches DEVONtechnologies' online discussion forum. Find answers to your most pressing questions regarding DEVONagent Pro & Co.
- **Yahoo Answers:** Looks for answers to user-posted questions on Yahoo Answers.

GOVERNMENT

- **USA.gov:** Searches for U.S. government information using FirstGov.gov. FirstGov.gov is the official U.S. gateway to all government information, with millions of webpages from federal and state governments, the District of Columbia and U.S. territories.

IMAGES & VIDEOS

- **Google Video:** Finds videos using Google Video.
- **Images:** Finds images using Google.com and Yahoo (including Flickr). Whatever image you are looking for, if it's on the Internet, you should be able to find it.
- **Picsearch:** Searches for pictures using Picsearch. Picsearch is a search engine specialized in creating a searchable index of images.
- **YouTube:** Searches for videos on the popular video clip service YouTube.

LEGAL

- **EUR-Lex:** Searches EUR-Lex for law documents and other public documents of the European Union. The contents of the site amount to more than 2.8 million documents with texts dating back to 1951. The database is updated daily and every year around 12,000 documents are added.
- **FindLaw:** Searches for legal materials using FindLaw. FindLaw is the highest-trafficked legal website, providing a comprehensive set of legal resources on the Internet for legal professionals, businesses, students and individuals.
- **Google Scholar (Case Law):** Searches for legal materials using Google Scholar. Google Scholar provides a way to broadly search for scholarly literature.
- **Lexis:** Searches for legal materials using Lexis. LexisNexis provides customers with access to billions of searchable documents and records from more than 45,000 legal, news, and business sources.

MEDICAL

- **Clinical Trials:** Searches for materials on ClinicalTrials. ClinicalTrials provides regularly updated information about U.S. federally and privately supported clinical research on human volunteers.
- **FDA:** Searches for material on the website of the U.S. Food and Drug Administration. The index is updated every night as many FDA documents are time sensitive.
- **Healthfinder:** Searches for health-related materials using Healthfinder. Healthfinder is a gateway to selected consumer health and human services information resources provided by government agencies and other organizations.
- **MedlinePlus:** Searches for health-related materials using MedlinePlus. MedlinePlus brings together authoritative information from the National Library of Medicie (NLM), the National Institutes of Health (NIH) and other government agencies and health-related organizations.

- **PubMed:** Searches the PubMed bibliographic database. PubMed provides access to bibliographic information that includes MEDLINE and OLDMEDLINE, as well as out-of-scope citations, citations that precede the date that a journal was selected for MEDLINE indexing, and some additional life science journals that submit full text to PubMedCentral and receive a qualitative review by the NLM.
- **WebMD:** Searches for health-related materials using WebMD. WebMD provides valuable health information, tools for managing your health and support to those who seek information.

NEWS

- **BBC News:** Searches for news on BBC News.
- **Google News:** Searches for news using Google News. Google uses its own search engine to scan important news websites and automatically compile a news portal using the found data.
- **Reuters:** Searches for news on the Reuters news database. Reuters is a global information company providing information tailored for professionals in the financial services, media, and corporate markets.
- **RocketNews:** Searches for news using Rocketinfo. Rocketinfo continuously searches and indexes over 16,000 Internet sites, 70,000 RSS and blog sources, as well as client-defined content channels, for current news and business information.
- **Topix:** Searches for news using Topix. Topix provides a news portal that aggregates news from other sources.
- **WorldNews:** Searches for news on the World News Network. World News Network ranks as one of the top sites for world news on the Internet. It includes more than 3,000 sites and covers 24 languages, categorized by geography and subject.
- **Yahoo:** Searches for news on Yahoo News. Yahoo uses its own search engine to scan important news websites and automatically compile a news portal using the found data.

PATENTS

- **Google Patent Search:** Covers the entire collection of patents made available by the USPTO, from patents issued in the 1790s through those issued in the middle of 2006. It doesn't include patent applications, international patents, or U.S. patents issued over the last few months.
- **US Patent Office:** Searches for patents on the US Patent and Trademark Office homepage.

REFERENCES

- **British Library:** Searches the British Library.
- **Google Scholar (Articles):** Searches for scholarly literature using Google Scholar. Google Scholar indexes scholarly literature across many disciplines and sources.
- **Googlism:** Lists the 'knowledge' stored in the Google database about a given search word. Googlism will find out what Google thinks of you, your friends or anything else.

- **Gutenberg.de:** Searches for literature in the German-language Project Gutenberg database of free ebooks.
- **Gutenberg.org:** Searches for literature in the English-language Project Gutenberg database of free ebooks.
- **Highbeam:** Searches for articles on Highbeam Research. HighBeam regards itself as the premier online research tool for business and academic use, with more than 80 million articles culled from the archives of over 6,500 newspapers, magazines, journals, and other publications.
- **Internet Public Library:** Searches for literature in the The Internet Public Library. The Internet Public Library is a public service organization and a learning and teaching online environment at the University of Michigan School of Information.
- **JSTOR:** Searches for articles on JSTOR. With more than a thousand academic journals and over 1 million images, letters, and other primary sources, JSTOR claims to be one of the world's most trusted sources for academic content.
- **Philosophy:** Searches for literature in the Stanford Encyclopedia of Philosophy.The Stanford Encyclopedia of Philosophy is maintained and kept up-to-date by an expert or group of experts in the field.
- **Poetry:** Searches for English poetry using the Electronic Poetry Center, founded by Loss Pequeno Glazier and Charles Bernstein.
- **SEC:** Searches the EDGAR database of the SEC.
- **Wikipedia:** Searches for articles in the free online encylopedia Wikipedia. The content of Wikipedia is free and is written collaboratively by people from all around the world. Begun in 2001, Wikipedia has grown rapidly into the largest reference website on the Internet. This plugin is localized and searches in the selected language.

SCIENCE

- **American Chemical Society:** Searches for materials on the American Chemical Society (ACS) website. The American Chemical Society is a self-governed individual membership organization that consists of more than 158,000 members at all degree levels and in all fields of chemistry.
- **IngentaConnect:** Searches online journals using IngentaConnect. IngentaConnect publishes scholarly and professional journals in all subject areas. It supports and produces more than 3,000 online journals.

SHOPPING

- **Amazon:** Searches for articles on Amazon. Chooses Amazon in the USA, Germany, or France depending on the system language.

SOCIAL NETWORKING

- **Twitter:** Searches for tweets on Twitter. No available on macOS High Sierra as access to system-wide social accounts is no longer possible.
- **Facebook Profiles:** Searches Facebook profiles.

> Note: The *Twitter* plugin is not available when you purchased DEVONagent Pro in the Mac App Store due to sandboxing restrictions.

LIST OF SCANNERS

Scanners do not query search engines, but rather filter webpages that do not match their criteria. For example, scanners can filter all pages that do not contain links to images or Office documents, pages that do not contain email addresses, or pages that have no embedded images. You can also use scanners to restrict search runs to Atom/RSS/JSON feeds, pages with linked documents, or to thumbnail galleries. Scanners filter out all pages that do not match.

Also, scanners are used by the sidebar of web browser windows to filter certain elements and display them lists, e.g. links, images, or news feeds.

By default, DEVONagent Pro comes with the following scanners that you can use in search sets.

- **All Links:** Lists all links of a page, e.g., those found by a secondary query.
- **Atom, RSS & JSON Feeds:** Looks for linked Atom, RSS, and JSON news feeds.
- **Audio files:** Looks for linked or embeddedaudio files and audio streams.
- **Code:** Looks for code snippets.
- **Email Addresses:** Looks for email addresses and recognizes even non-linked and scrambled addresses like "info at devon-technologies dot com".
- **Embedded Images:** Lists all images of the page, e.g., those found by a secondary query.
- **Linked BibTeX & LaTeX Files:** Looks for linked BibTeX and LaTeX files.
- **Linked Binary Files:** Looks for linked downloadable compressed archives and disk images.
- **Linked Documents:** Looks for linked PDF, PostScript, OpenOffice, StarOffice, WordPerfect, Microsoft Word, Microsoft PowerPoint, or text documents.
- **Linked Scripts:** Looks for linked AppleScript scripts.
- **Linked Spreadsheets:** Looks for linked spreadsheet files (XMLSS, Microsoft Excel, CSV, TSV).
- **Linked Vcard files:** Looks for linked business card files (.vcf).
- **Recipies:** Looks for cooking recipies.

- **Thumbnail Galleries:** Looks for images in an image gallery, but lets pass all pages containing (usually smaller) images linked to (usually larger) image files, a.k.a. thumbnail galleries.
- **Twitter Accounts:** Looks for links referencing unique Twitter IDs.
- **Video Files:** Looks for linked or embedded video files and streams.
- **Wallpapers:** Looks for desktop background pictures.
- **Webcams:** Looks for web cams and live streams.

LOG MESSAGE CODES

DEVONagent Pro logs all pages filtered out in the log, together with a short code describing why the page was filtered. Use the log tab of search windows to find out which pages have been dropped and for what reason.

HTTP ERROR CODES

These error codes are standard HTTP error codes delivered directly from web server that DEVONagent Pro asked for a file:

- **204:** No response
- **301:** Moved permanently
- **302:** Moved temporarily
- **401:** Authorization required
- **403:** Forbidden
- **404:** Page not found
- **408:** Request timeout
- **410:** Gone
- **500:** Internal server error
- **501:** Not implemented
- **502:** Service temporarily overloaded
- **503:** Gateway timeout
- **522:** Connection timed out

Wikipedia has a complete list of all possible HTTP error codes.

DEVONAGENT PRO ERROR DESCRIPTIONS

These errors appear in the log when communication problems with the web server occurred, or, more likely, when DEVONagent Pro filtered the page out due to search strategy or user-defined settings.

- **Advertisements:** Link or frame probably contains only advertisement or banners
- **Archived:** Identical page has already been archived (if "Archived Pages"filter is activated)

- **Disabled format:** Page isn't in a suitable format
- **Disallowed:** Page couldn't be downloaded due to permissions
- **Duplicate:** Identical page already found
- **Excluded:** URL or domain excluded by the user
- **Failed:** Search engine could not be reached
- **Filtered by scanner:** Page did not pass the selected scanner
- **Host not found:** Website not found
- **Identical:** Identical page with different URL already found
- **Incomplete:** Download could not be completed
- **Junk:** Page contains almost no useful information (if the article filter filter is activated)
- **Language:** Page does not match the language selected in the language filter
- **Links: x of y:** Pages delivered as a result by a search engine. Numbers indicate used links vs. returned links. If the number of used links is lower than the returned one, then either another search engine already returned the same link or the host is blocked.
- **Lookup failure:** Domain of website not found
- **No content:** Page does not contain any text
- **No match:** Page does not match the query term
- **Only links:** Only links matching the query term found (if *Follow Links* is activated)
- **SPAM:** Page tried to fool search engines, but does not match the query term without those tricks
- **Similar:** Similar page (different layout but similar text) with different URL already found (if *Similar Pages* is activated)
- **Skipped:** Domain was skipped because it matches one or more entries in the list of unwanted sites
- **Timeout:** Web server didn't respond in time
- **Too big:** Page is larger than the maximum size defined in the preferences
- **Unknown data:** No HTML or text content